Pioneer sound.vision.soul

PDP-4345HD

43" HIGH-DEFINITION PLASMA TELEVISION

- 43-inch High-Definition Television
- XGA Resolution (1,024 x 768p)
- 16:9 Wide-Screen Aspect Ratio Advanced PureCinema with 3:3 Pull Down
- First Plasma Capable of 72Hz Display
- Pure Drive Full Digital Image Processing
- ACE II (Advanced Continuous Emission Display II) for 1.07-Billion-Color Reproduction and Improved Grayscale Rendering in Dark Areas
- · Pure Color Filter I for Improved Color Accuracy with More Accurate Color than any CRT
- Ultra-Bright, 1,100 Cd/m²
- · Deep Encased Cell Structure with Black Stripe Coating
- Adjustable Color Temperature, 3 Settings w/6,500 Degrees (High/Mid/Low)

- · 2 Sets of HDMI Inputs
- · i.LINK, IEEE-1394 Digital Interface for **D-VHS Control**
- 3 Sets of Component Connectors
- Integrated ATSC Tuner
- 3-Dimensional Y/C Separation
- · World's First MPEG Noise Reduction (ON/OFF)
- · Stylish, Versatile Recessed 2-Way Speaker Design for Side and Under Mounting
- Split Screen or Picture in Picture Function for HDTV, NTSC and Various Other Signal Sources (NTSC, HD, PC)
- Three Surround Modes (SRS/FOCUS/ TruBass)

side view

· HD Converter for Clear, Natural-Looking Images

- · World's First Natural Enhancer for Clear. **Smoother Edges**
- Dynamic Range Expander (ON/OFF)
- Digital Noise Reduction in 3 Steps
- · Closed Captioning and V-Chip System
- 5 Selectable Screen Modes
- · Illuminated Preset/Learning Remote Control
- Antenna Input A: NTSC/ATSC/DCR (75 ohms Unbalanced F Connector) Antenna Input B: NTSC (75 ohms Unbalanced F Connector)
- Antenna Output, VHF/UHF x 1 (75 ohms Unbalanced F Connector)
- A/V Input (Front x 1, Rear x 2) (RCA Pin)
- S-Video Input (Front x 1, Rear x 2)
- S-Video Output (Rear x 1)

- Component Input (Front x 1, Rear x 2)
- D-Sub 15 Input (Front) x 1 (for PC Input)
- Digital Audio Output (Rear), Optical
- SR In/Output (Out=SR+)
- Optional 10-Meter Digital Connection Cable
- Optional Flush Mount Wall Bracket
- Optional Tilt Wall Bracket
- 1-Year Warranty, Residential Application Only (Image Persistence not Covered)
- Power Requirements: AC 120V
- Dimensions (W x H x D): 44-1/8 x 25-11/16 x 3-7/8 inches/1,120 x 652 x 98mm (Display), 16-9/16 x 3-9/16 x 11-5/8 inches/420 x 90 x 295mm (Media Receiver)
- Weight: 67 lbs. 4 oz./30.5kg (Display), 12 lbs. 9 oz./5.7kg (Media Receiver)







· Specifications and design subject to modification without notice

· Displaying the same still images for long periods should be avoided as image shadowing or burn-in

Media Receiver, Side Speakers and Table-top Stand are included

PureVision and PureCinema are registered trademarks of Pioneer Corporation

High-Definition Television (HDTV): HDTV refers to a complete product/system with the following minimum performance attributes: ". Receiver: Receives ATSC terrestrial digital transmissions and decodes all ATSC Table 3 video formats · Display Scanning Format: Has active vertical scanning lines of 720 progressive (720p), 1,080 interlaced (1,080i) or higher · Aspect Ratio: Capable of displaying a 16:9 image · Audio: Receives and reproduces, and/or outputs Dolby Digital audio " Consumer Electronics Association, August 2000

· HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.

i.I.INK and the i.I.INK logo are trademarks of Sony Corporation

 Dolby and the double-D symbol are registered trademarks of Dolby Laboratories. SRS WOW, SRS and () symbol are trademarks of SRS Labs, Inc.

SRS, TruBass and EOCUS are trademarks of SRS Labs, Inc.

may occur