



32AV700 SPECIFICATIONS

MODEL	32AV700
MAIN	
Product Type	LCD TV
Screen Type	32
Dynamic Contrast Ratio	50000:1
Resolution (H x V)	1366 X 768
VISUAL	
Video Engine	Power Meta Brain
Video processing	10 Bit video processing
24p	○
3D Colour Management	○
Comb Filter	3D Y/C
Intelligent Backlight Control	○
Mpeg Noise Reduction	○
Real Digital Picture	○
Media Playback	Jpeg
Picture Mode	Autoview/ Dynamic/ Standard/ Mild/ Movie/ Game/ PC
RF booster	○
AUDIO	
Stereo System	NICAM / A2 Stereo
Super Woofer System	Bass Boost
Audio Output	5W x 2
FEATURES	
Autoview	○
Ambient Light Sensor	○
Teletext	○
Multilingual OSD	English / French / Russian / Simplified Chinese/ Thai / Malay / Vietnamese / Arabic/ Persian
Picture in Picture	-
Hotel Mode**	○
REGZA Link	-
Swivel Stand	Fixed Stand
CONNECTION	
Antenna Input	1
EXT 1	Input: Composite Video + RCA Audio
EXT 2	Input: Component Video + RCA Audio
EXT 3	Input: HDMI 1
EXT 4	Input: HDMI 2
EXT 5	Input: HDMI 3
EXT 6	Input: HDMI 4
EXT 7	PC Input
EXT 8	-
EXT 9	-
PC Input	D-Sub 15 Pin + 3.5mm Mini Jack (Common with HDMI 1 Audio)
Output	RCA Audio
Digital input	USB (Jpeg Playback)
Headphone	-
RS-232C	-
SIGNALS	
Receiving System	PAL I/ BG/ DK, SECAM BG/ DK, NTSC M/ BG 4.43
Video Signal	480i/480p (60Hz), 576i/576p (50Hz), 720p (50/60Hz), 1080i (50/60Hz), 1080p (24/50/60Hz) through HDMI
RGB Signal*	VGA, SVGA, XGA, WXGA, SXGA
GENERAL	
Automatic Voltage Regulator	E: 220-240V 50/60Hz T: 110-240V 50Hz V: 110-240V 50Hz
Power Consumption (W)	90
Dimension (W x H x D) mm without Stand	786 x 525 x 78
Dimension (W x H x D) mm with Stand	786 x 568 x 221
Weight (Net) kg without Stand	9.0
Weight (Net) kg with Stand	10.0
OPTIONAL ACCESSORIES	
Wall Mount Bracket	WAL13C

* These signal formats are converted to match the number of pixels of the panel. Small text may not be displayed properly.

** Hotel Mode is designed for use in hotels only.

Design and specifications are subject to change without prior notice