

DISPLAY

AVAILABLE COLORS



Silver



Black



SHOWN IN BLACK WITH OPTIONAL SPEAKERS

KEY FEATURES

- 47" Marquee Series True Outdoor All-Weather Digital Signage Display.
- Landscape installation only, for portrait installation use DS-4707ESTP.
- Direct Sunlight-Readable 700 NIT LCD screen.
- High temperature Enhanced Solar Tolerance (EST) technology prevents isotropic blackout.
- Exterior designed to protect internal components from rain, dust, insects, humidity, and salt air.
- Multi-fan airflow system keeps the unit cool & dry in temperatures up to 122 degrees F.
- Ability to operate in cold weather (-40 degrees F).
- Front tempered anti-reflective glass window provides added protection to LCD screen, and safeguards against vandalism and abuse.
- Full command control, RS232 and Discrete IR located in cable-entry compartment.
- Innovative water-tight Cable Entry System seals out moisture and allows for easy hook-ups.
- Internal media compartment to house DMP, Pro:Idiom boxes, or fan-less PC's (optional).
- Powder-coated aluminum exterior.
- Weatherproof detachable 20W speaker module (optional).
- Weatherproof control buttons.
- Remote Control Lock-Out prevents unauthorized users from changing the programming.

<p>SCREEN</p>	<p>LCD SCREEN 47-inch diagonal TFT Active Matrix</p> <p>RESOLUTION 1920 x 1080 Full-HD 1080p</p> <p>ASPECT RATIO 16:9</p> <p>CONTRAST RATIO 4000:1</p> <p>FRAME RATE 120 Hz</p>	<p>VIEWING ANGLE 176° x 176°</p> <p>RESPONSE TIME 9.0 milliseconds</p> <p>TV FORMATS 1080p, 1080i, 720p, 480p, 480i</p> <p>SCREEN ORIENTATION Landscape Mode</p>
<p>CONNECTIONS</p>	<p>RF Antenna/CATV (ATSC/QAM/NTSC) x1</p> <p>HDMI HDMI™ Input x2</p> <p>VIDEO COMPOSITE S-Video x1 and Composite Video x1, L/R Audio Inputs x1</p> <p>VIDEO COMPONENT YPbPr plus Stereo Audio x2</p> <p>PC 15-pin D-sub VGA plus Stereo Audio</p>	<p>CONTROL SET RS232 Serial, Discrete IR Control, Concealed IR Window</p> <p>AUDIO OUT SPDIF Audio, Analog 1/8" headphone jack.</p> <p>SPEAKERS 20 WATT detachable speaker module (optional).</p> <p>INPUT POWER 100-240 VAC, 50-60 Hz 2.8 A Max</p>
<p>TEMPERATURE TOLERANCES</p>	<p>OPERATING TEMP -40° to 122° F. (-40° to 50°C.)</p> <p>NON-OP. TEMP -40° to 140° F. (-40° to 60°C.)</p> <p>(OFF MODE WITH POWER APPLIED) The non-operating temperature feature requires power to be applied.</p>	
<p>PHYSICAL SPECS</p>	<p>ACCESSORIES INCLUDED Weatherproof remote control.</p> <p>EXTERIOR Powder-coated aluminum.</p> <p>EXTERIOR COLORS Black, Silver</p> <p>TV DIMENSIONS 44.72"W x 29.33"H x 6.85"D (w/ speaker module)</p> <p>TV WEIGHT 70.0 lbs.</p>	<p>SHIPPING DIMENSIONS 52.0"W x 42.0"H x 13.0"D</p> <p>SHIPPING WEIGHT 125.0 lbs.</p> <p>RESIDENTIAL WARRANTY Two-year parts and labor.</p> <p>COMMERCIAL WARRANTY One-year parts and labor.</p>