





UltraVision® 55" LCD HDTV

Key Features

- 1280 x 720p High-Definition Display¹
- High-Contrast Dual Focus Lens System
- Ultra-Compact LCD 3-Panel Light Engine
- Exclusive 7:1 Fresnel Lens
- VirtualHD™ 1080p II Video Processor -Dynamic Contrast
 - -Dynamic Histogram Processing
 - -12 Bit/68 Billion Color Capability -Automatic 1080i 3:2 Film
 - Processing
 - -26-Point Advanced Video Processing
 - -3 HD Aspect Modes
 - -6 SD Aspect Modes
 - -1080i/720p/480p/480i Input Compatible
 - -HD Digital Window™ Split Screen
- Anti-Reflective High-Contrast Diffusion Screen
- Quick Start Seamless HDTV and NTSC Tuners
- Digital Cable-Ready and CableCARD™ Compatible²
- First-Surface Mirror
- 4-Color Temperature Memory
- B&W Film Color Temperature
- 4-Step Black Enhancement
- Digital 4MB 3D Y/C Comb Filter

Audio Performance Features

- MTS Stereo/SAP with dbx[™]
- SRS® Surround Sound
- BBE® Sound Enhancement
 40-Watt 3-Way Speaker System
- Mute and Soft Mute
- TV-as-Center Speaker

Convenience Features

- Preprogrammed Remote Control
 Day and Night Memory by Input with Timer
- Side Panel Menu Controls
- 181-Channel NTSC Tuner
- 3-Language On-Screen Display
- Parental Locks (V-Chip)
- Closed Caption Decoder
- On/Sleep Timers
 AutoLink Input Sensor
- Discrete IR Codes

Innuts/Outnuts

iiiputs/Outputs
CableCARD™ Interface:1
 HDMI™ High-Definition
Multimedia Interface:32
 Wideband Component
Video Inputs:
 S-Video Inputs (Rear/Side):2/1
 AV Inputs (Rear/Side):4/1
Antenna Inputs:
Center Channel Input: All Inputs
· (L/Mono)
AV Output with S-Video:
Optical Digital Output:
Fixed/Variable Audio Output:1

Specifications

•	Color:		Ме	tallic	BI	ack
•	Resolution:	1280	$(H) \times$	720 (V)	х3

Dimensions

Monitor With Optional F	loor Stand
 Height 	52 ³ /8'
• Width	59 ⁷ /8
 Depth 	17 3/4'
Monitor Without Optiona	al Floor Stand
Monitor Without Options Height	
	31 ¹ /s'
Height	31 ¹ /8 ¹ 59 ⁷ /8

Optional Accessories

Optional Floor Stand: SPT55Replacement Lamp: TBA

Warranty

- 1 Year Parts and Labor Warranty - In-Home Service
- More than 94% of the 720 signal is displayed. Due to variances in program productions and transmissions not all of the 720 signal is suitable for display.
- This digital television is capable of receiving basic analog, digital basic and digital premium cable television programming by direct connection to a cable system providing such programming. A security card (CableCARD) provided by your cable operator is required to view encrypted digital programming. Certain advanced interactive digital cable services may require the use of a set top box: video-on-demand, cable operator enhanced program guide, data enhanced television service. For more information contact your local cable operator.
 BIMI inputs are compatible with DVI-HDTV
- 3 HDMI inputs are compatible with DVI-HDTV (HDCP) signals when combined with an adapter cable. Adapter cable is not included. All trademarks are the property of their respective owners.

Respective owners.

All specifications and dimensions are subject to change without notice. Refer to www.hitachi.us/tv for updated custom installation specifications.