

CRYSTAL SERIES™



CR-26HD



CR-32HD



CR-40HD

RUNCO
THE WORLD'S FINEST
HOME THEATER PRODUCTS™



CR-40HD

Runco presents a broad range of high performance WideVision™ LCD displays perfect for those who demand our award-winning flat panel performance in more intimate sizes than we offer with our larger plasma monitors.

These new high definition HDTV-ready displays all offer common features and performance in popular 26, 32 and 40-inch sizes suitable for close-in viewing where picture quality remains a high priority, but larger displays cannot be accommodated.

All of the Crystal Series models incorporate the same superb Vivix™ digital video processing recently developed for our “MC” series of plasma monitors, producing outstanding picture quality with a wide range of both standard and high definition source material.

In addition, these handsome, gloss black televisions are engineered with ISF™ calibration standards in every model for the purest video performance. The CR-26HD and CR-32HD also feature an advanced, 185 channel cable-ready NTSC stereo tuner offering PIP, POP, closed captioning, V-chip functionality and multi-language support. All three models include integrated stereo audio systems incorporating surround sound technology with 2-way speakers and generous power amplification.

The advanced TFT active matrix LCD display panels offer 1366 x 768 resolution on all models and include Runco’s discrete aspect ratio control with VirtualWide™ mode to fill the 16:9 screen with standard 4:3 images without loss of picture quality. Also included are discrete source, aspect ratio and power selection and an RS-232 interface for whole house or automated control system integration.

The Crystal Series are also multimedia ready, with simple computer connections making gaming, internet browsing and other computer activities quick and easy.

SPECIFICATIONS:	CR-26HD	CR-32HD	CR-40HD
Native Resolution:	1366 x 768 WXGA	1366 x 768 WXGA	1366 x 768 WXGA
Screen Size:	26 in. (diagonal)	32 in. (diagonal)	40 in. (diagonal)
Screen Aspect Ratio:	16:9	16:9	16:9
Available Aspect Ratios:	4:3, Letterbox, 16:9 Anamorphic, VirtualWide™	4:3, Letterbox, 16:9 Anamorphic, VirtualWide™	4:3, Letterbox, 16:9 Anamorphic, VirtualWide™
DTV Compatibility:	480p, 720p, 1080i	480p, 720p, 1080i	480p, 720p, 1080i
ISF Settings:	Yes	Yes	Yes
Contrast Ratio:	1000:1	1000:1	800:1
Data/Graphics Compatibility:	Up to 1024 x 768	Up to 1024 x 768	Up to 1024 x 768
Vivix Processing:	3:2 pull down	3:2 pull down	3:2 pull down
Inputs:	Multiple input combinations with up to (4) Composite, (2) S-Video, (2) Component, (1) DVI w/HDCP, (1) RGB (15-pin mini D-sub), (1) RS-232, (4) Audio (stereo RCA pairs), (1) RF Antenna	Multiple input combinations with up to (4) Composite, (2) S-Video, (2) Component, (1) DVI w/HDCP, (1) RGB (15-pin mini D-sub), (1) RS-232, (4) Audio (stereo RCA pairs), (1) RF Antenna	Multiple input combinations with up to (4) Composite, (2) S-Video, (2) Component, (1) DVI w/HDCP, (1) RGB (15-pin mini D-sub), (1) RS-232, (4) Audio (stereo RCA pairs), (1) RF Antenna
Outputs:	(1) Composite, (1) Audio (stereo RCA pair)	(1) Composite, (1) Audio (stereo RCA pair)	(1) Composite, (1) Audio (stereo RCA pair)
Audio System:	10W RMS x 2, L/R two-way Integrated Speaker System	10W RMS x 2, L/R two-way Detachable Speaker System	10W RMS x 2, L/R two-way Detachable Speaker System
Tuner:	185 CH. NTSC Stereo (PAL as monitor only) HDTV Ready, PIP/POP, V-chip, Closed Caption	185 CH. NTSC Stereo (PAL as monitor only) HDTV Ready, PIP/POP, V-chip, Closed Caption	Monitor only — no tuner.
Discrete IR Control:	Source, power and aspect ratios	Source, power and aspect ratios	Source, power and aspect ratios
Power Requirements:	100-240V AC, 50/60Hz	100-240V AC, 50/60Hz	100-240V AC, 50/60Hz
Power Consumption:	130W	180W	280W
Operating Environment:	40 to 95°F (5 to 35°C); 20-80% humidity (non-condensing)	40 to 95°F (5 to 35°C); 20-80% humidity (non-condensing)	40 to 95°F (5 to 35°C); 20-80% humidity (non-condensing)
Dimensions:	Width: 27 in. Depth: 3 3/8 in. (w/stand 7 9/16) Height: 19 1/2 in. (w/stand 20 in.) Weight: 26.46 lbs. with stand	Width: 31 3/8 in. (w/spkrs. 38 1/8 in.) Depth: 4 1/2 in (w/stand 9 27/32 in) Height: 19 1/2 in. (w/stand 21 3/4 in.) Weight: 50.71 lbs. with stand	Width: 39 in. (w/spkrs. 45 3/4 in.) Depth: 4 1/2 in (w/stand 9 27/32 in) Height: 23 1/2 in. (w/stand 25 1/8 in.) Weight: 68.34 lbs. with stand
Regulatory Approvals:	Complies with FCC, CE, C-Tick	Complies with FCC, CE, C-Tick	Complies with FCC, CE, C-Tick
Limited Warranty:	(1) One year parts and labor from the date of delivery to the end user.	(1) One year parts and labor from the date of delivery to the end user.	(1) One year parts and labor from the date of delivery to the end user.