

Akira DLT Series Specifications



| Product Name | | DLT-260W | DLT-270W | DLT-300W | DLT-320W | DLT-400W |
|----------------------|---|--|---|-----------------------------------|------------------------------------|-------------------------------------|
| Screen Size | | 26" | 27" | 30" | 32" | 40" |
| LCD Panel | Aspect Ratio | 15:9 | | | 15:9 | |
| | Resolution | 1280 x 720 | | | 1280 x 768 | |
| | Brightness | 450cd/m ² | 500cd/m ² | | 450cd/m ² | |
| | Contrast Ratio (Dark room) | 500:1 | | | | 600:1 |
| | Screen Size (H×V) | 22.3" x 13.4" 566.4 x 339.84mm | 23.5" x 13.2" 597.12 x 335.88mm | 25.5" x 15.4" 648.8 x 391.52mm | 27.1" x 16.2" 687.36 x 412.42mm | 34.3" x 21.6" 871.68 x 523.008mm |
| | Cell Pitch (H×V) | 0.4425 x 0.4425mm | 0.4665 x 0.4665mm | 0.5025 x 0.5025mm | 0.537 x 0.537mm | 0.681 x 0.681mm |
| | Viewing Angle | Over 170° | | | | |
| | Displayable Colors | 16.77 Million | | | | |
| Response Time | 15/8mS | | | | | |
| Input Features | Analog RGB (PC) | 1 | D-Sub 15Pin | | | |
| | Component (Y, Pb/Pb, Cr/Pr), DVD/DTV Input | 1 | 480i, 480P, 720P, 1080i | | | |
| | AV Input | 2 | CVBS(1 on Rear, 1 on Side) | | | |
| | Y/C (S-Video) Input | 2 | 4Pin Din (1 on Rear, 1 on Side) | | | |
| | Audio Input (R,L) | 3 | CVBS/S-Video (2), Component | | | |
| | RF | 1 | AIR/Cable Tuner | | | |
| | SCART | 1 | FULL 21Pin Euro AV (Only for PAL, SECAM Type) | | | |
| Output Features | | 1 | 6W+6W RMS (4Ω)External Speaker Out L/R (2 Way, 4-Speakers) | | | |
| | Headphone Jack | 1 | Volume Adjustable/ on Side | | | |
| Front Panel Controls | Input Select , Menu, Volume 5/6, Channel 5/6, Power | | | | | |
| Video | Display Formats | 16:9/4:3/Zoom/Panorama | | | | |
| | Video Preset Mode | Standard/Sport/Natural/Mild/Custom | | | | |
| | PC-Format | VGA, SVGA, XGA | | | | |
| | Features | Genesis Scaler, Motion-Adapte function, Progressive Scan Conversion, | | | | |
| Audio | Preset Mode | Standard/Music/Film/Speech/Custom | | | | |
| | Amplifier | 4.5W+4.5W Stereo | | | | |
| | Speaker | Detachable, Side Mount or Stand up 2-Way/4Speakers | | | | |
| | Features | 5-band Equalizer, Sound Effect(Pseudo/Surround) Sound Encoding(Stereo/Dual 1 &2) | | | | |
| TV | Tuner | 1 | NTSC AIR/Cable Tuner | | | |
| | Features | Favorite Channels, Channel Memory | | | | |
| OSD Languages | Multi-Language Support | English/French/German/Italian/Spanish | | | | |
| Misc | RS-232C | N/A | | | | |
| | TCP/IP | N/A | | | | |
| | Menu System | Smart OSD | | | | |
| | Features | 0-180 Minutes Sleep timer, ON/OFF Timer, No-Key Auto Off, No signal Auto Off, Key Lock, Picture Noise Reduction, Frozen screen, OSD Display Time set | | | | |
| Input Voltage | AC 100~240V, 50Hz/60Hz | | | | | |
| Power Consumption | Operation | 147W | 117W | 115W | 160W | 243W |
| | Stand- By | <5W | | | | |
| Dimensions | Size (W×H×D) | 833x432x100 | 854 x 423 x 89mm | 902 x 475 x 103mm | 950 x 475 x 103mm | 1139 x 620 x 105mm |
| | Size with Stand | 833x462x203 | 854 x 453 x 203mm | 902 x 505 x 203mm | 950 x 536 x 203mm | 1139 x 650 x 203 |
| | Weight(with Stand) | 13Kg | 14Kg | 16Kg | 18Kg | 33Kg |
| Accessories | Stand & Speaker are Included / Wall mount Optional | | | | | |