

DView[™]
LCD[™] Flat Panel Monitors

Vidikron introduces the VL-26, VL-32, and VL-37 DView[™] flat panel high definition displays.

This new Vidikron Series of LCD HDTV Displays has been designed for the discriminating enthusiast with the highest video quality expectations. In keeping with Vidikron's commitment to excellence, we have incorporated numerous custom installation-friendly features such as comprehensive ISF calibration capabilities, a generous assortment of inputs plus full integration ability with today's latest and most advanced home automation systems. Each DView monitor includes Vidikron's exclusive Imagix™ processing technology to produce stunning images from any source.

All three high definition displays are wrapped in the Vidikron 'pewter finish' to suit any home décor.



	VL-26	VL-32	VL-37
LCD Display:	26" diagonal, 16:9	32" diagonal, 16:9	37" diagonal, 16:9
Native Resolution:	1366 x 768 WXGA	1366 x 768	1366 x 768
Contrast Ratio:	1000:1	1000:1	1000:1
Available Aspect Ratios:	4:3, Letterbox, 16:9 Anamorphic, IntelliWide™	4:3, Letterbox, 16:9 Anamorphic, IntelliWide™	4:3, Letterbox, 16:9 Anamorphic, IntelliWide™
DTV Compatibility:	480i, 480p 576i, 576p 720p, 1080i	480i, 480p 576i, 576p 720p, 1080i	480i, 480p 576i, 576p 720p, 1080i
ISF Settings:	Yes	Yes	Yes
Data/Graphics Compatibility:	Up to 1024 x 768	Up to 1024 x 768	Up to 1024 x 768
Imagix™ Processing:	3:2 pull down	3:2 pull down	3:2 pull down
Inputs:	Multiple input combinations with up to (4) Composite, (2) S-Video, (2) Component, (1) DVI w/HDCP, (1) RGB (15-pin D-sub), (1) RS-232, (5) Audio (stereo RCA pairs), (1) RF Antenna	Multiple input combinations with up to (4) Composite, (2) S-Video, (2) Component, (1) DVI w/HDCP, (1) RGB (15-pin D-sub), (1) RS-232, (5) Audio (stereo RCA pairs), (1) RF Antenna	Multiple input combinations with up to (4) Composite, (2) S-Video, (2) Component, (1) DVI w/HDCP, (1) RGB (15-pin D-sub), (1) RS-232, (5) Audio (stereo RCA pairs)
Outputs:	(1) Composite, (1) Audio (stereo RCA pair)	(1) Composite, (1) Audio (stereo RCA pair)	(1) Composite, (1) Audio (stereo RCA pair)
Audio System:	10W RMS x 2, L/R two-way Integrated Speaker System	10W RMS x 2, L/R two-way Integrated Speaker System	10W RMS x 2, L/R two-way Integrated Speaker System
Tuner:	185-channel NTSC Stereo (PAL as monitor only) HDTV Ready, PIP/PBP, Parental Control (V-Chip), Closed Caption	185-channel NTSC Stereo (PAL as monitor only) HDTV Ready, PIP/PBP, Parental Control (V-Chip), Closed Caption	Monitor only. No tuner.
Discrete IR Control:	Source, power and aspect ratios	Source, power and aspect ratios	Source, power and aspect ratios
Power Requirements:	100 to 240 VAC, 50/60Hz	100 to 240 VAC, 50/60Hz	100 to 240 VAC, 50/60Hz
Power Consumption:	130W	180W	230W
Operating Environment:	40°F to 95°F (5°C to 35°C); 20% to 80% humidity (non-condensing)	40°F to 95°F (5°C to 35°C); 20% to 80% humidity (non-condensing)	40°F to 95°F (5°C to 35°C); 20% to 80% humidity (non-condensing)
Dimensions:	Height: 19 7/8 in. (505.00 mm) Width: 27 in. (686.00 mm) Depth: 3 1/2 in. (88.90 mm) Weight: 26.46 lbs. (12.00 kg)	Height: 23 1/32 in. (585.00 mm) Width: 31 11/16 in. (805.00 mm) Depth: 3 7/8 in. (98.00 mm) Weight: 50.71 lbs. (23.00 kg)	Height: 22 1/16 in. (560.00 mm) Width: 42 1/2 in. (1080.00 mm) Depth: 3 15/16 in. (99.00 mm) Weight: 68.34 lbs. (31.00 kg)
Regulatory Approvals:	Complies with FCC, UL	Complies with FCC, UL	Complies with FCC
Limited Warranty:	One (1) year parts and labor from the date of delivery to the end user.	One (1) year parts and labor from the date of delivery to the end user.	One (1) year parts and labor from the date of delivery to the end user.







Specifications are subject to change without notice. Optional table stand or wall mount available.

© 2006 Vidikron, a Runco International Company. All rights reserved. Vidikron, DView, Intelliwide, and Imagix are trademarks of Vidikron. ISF is a registered trademark of Imaging Science Foundation.



Vidikron 2900 Faber Street Union City, CA 94587 510-324-5900 Fax 510-324-5905 www.vidikron.com