

# 37" LCD TV (HL-3710B) / NTSC

<b>ITEM</b>		<b>Sepecification</b>	
<b>Screen</b>	<b>Aspect Ratio</b>	16:9	
	<b>Screen size (HxV)</b>	877.0mm(H) x 516.8mm(V)	
	<b>Resolution</b>	1366 x 768	
	<b>Pixel Pitch</b>	0.600mm(H) x 0.600mm(W)	
	<b>Displayable Colors</b>	16.77 million	
	<b>Peak Bright</b>	500 cd/m2	
	<b>Contrast Ratio</b>	500:1	
	<b>Response Time</b>	25ms	
	<b>View angle</b>	176 deg	
<b>TV</b>	<b>Reception System</b>	NTSC	
	<b>RF System</b>	<b>Two Tuners alternative NTSC</b>	
	<b>Closed Caption</b>	Yes	
	<b>V-chip</b>	Yes	
	<b>Feature</b>		Dual Channel Swapping
			Channel Digest (15 Windows)
			True PIP&PBP (Dual Screens)
			Auto Channel Preset
			Auto Channel Sort
			Advanced Motion Digital Processor
			HD Signal De-Interlacing
			3:2 Pull down for Film Scan Conversion
			Digital Progressive Line Scaling
			Favorite Channel Programming
			DVI HDCP (Optional)
	Motion Adaptive Deinterlace Processor		
	Automatic Frequency Detection		
	Selectable User Color Adjustment		
<b>User Control</b>	<b>Power Key</b>	Power (Main/ST-BY)	
	<b>Function Key</b>	INPUT SELECT, Vol. +/-	
	<b>OSD Language</b>	English, German, French, Spanish, Italian, Portugal, Russian	
<b>I/O Ports</b>	<b>TV Input</b>	RF / CATV (NTSC)	
	<b>AV 1,2 Input</b>	AV1, AV2	
	<b>Composite Input/Output</b>	RCA x 2Port (AV3 Input, AV Output)	
	<b>Component 1,2 Input</b>	RCA x 2Port (480i/p, 576i/p, 720p, 1080i)	
	<b>S-Video Input</b>	Mini Din 4Pin x 1 Port	
	<b>PC Input</b>	Mini D-Sub 15Pin x 1 port / HDTV Input	
	<b>DVI Input</b>	Mini D-Sub 29Pin x 1 port / HDTV Input	
	<b>Audio In / Out</b>	RCA x 5 Port	
	<b>Speaker Output</b>	Cinch Type x 1 Port(Stereo L/R)	
	<b>External Control Port</b>	External Control Port Mini D-Sub 9Pin x 1port	
<b>AC Input</b>		110 ~ 240V, 50Hz ~ 60Hz	
<b>Dimension / Weight</b>	<b>Main Only</b>	915(W) x 557(H) x 102(D) / 24Kg	
	<b>With Stand</b>	915(W) x 625(H) x 270(D) / 26Kg	
	<b>With Stand and Speaker</b>	1108(W) x 625(H) x 270(D) / 30Kg	