2011 VIERA® X30 Series LCD



Available Model: TC-L32X30

IPS ALPHA PANEL

Delivers a 178° wide viewing angle for bright and clear images from virtually anywhere in the room.

IPOD®/IPHONE® ENTERTAINMENT KIT

Control and play music and videos from your iPhone®/iPod®* on your VIERA HDTV.

EASY IPTV

Enjoy great Web entertainment with just a click of your remote.

VIERA IMAGE VIEWER (PHOTO & MOVIE)

View digital photos and videos on your VIERA HDTV.

- 720p HD Resolution
- 60 Hz Refresh Rate
- Fine Black Panel
- Game Mode
- DLNA

- VIERA Link™
- 3 HDMI
- 1 USB
- PC Input

















2011 VIERA° X30 Series LCD

		TC-L32X30
VIDEO		10 202A00
Screen Size Diagonal (in)		31.5
Aspect Ratio		16:9
Panel		IPS Alpha LCD (WXGA)
Filter		Fine Black Panel
Number of Pixels		1,049,088 (1,366 x 768)
Moving Picture Resolution		300 lines
Viewing Angle		178 degrees
HDTV Display Capability (1080p, 1080i, 720p)		Υ
EDTV Display Capability (480p)		Υ
Aspect Control		480i/ p: FULL, JUST, 4:3, Z00M
Progressive Scan		1080i/ p: FULL, H-FILL, JUST, 4:3, Z00M
Progressive Scan Panel Drive		Y
24p Smooth Film		60 Hz
24p Playback		- Y
x.v.Color		
Intelligent Scene Controller		Υ
Motion Focus Technology		
Super Resolution		Υ
FULL HD 3D		
3D Panel		_
3D 24p Smooth Film		_
2D-3D Conversion		_
3D Image Viewer		_
3D Active Shutter Eyewear		_
AUDIO		
Speakers		Full-range x 2 (L, R)
Number of Speakers		2
Audio Output		20 W
Surround Sound		V-Audio Surround
JACKS		
Integrated ATSC Tuner		Υ
VIERA Image Viewer		Y (AVCHD/ MPEG2/ JPEG/ MP3 playback)
HDMI	Input	3 (1 side)
Luca	Support Feature	Audio Return Channel (Input 1)
USB		1
Analog Audio Input (for HDMI/DVI)		Υ
Composite Video Input		RCA x 1
Audio Input (for Video)		RCA x 1
PC Input Component Video Input (Y, PB, PR)		D-sub 15-pin x 1 RCA x 1
Audio Input (for Component Video)		RCA x 1
LAN Port		1
Digital Audio Output		1 (5.1 ch)
CONVENIENCE		
VIERA Link		Υ
VIERA Connect (IPTV)		_
Easy IPTV		Υ
Wireless LAN Adaptor		Wi-Fi Ready
Universal Dock for iPod		Υ
VIERA Tools		Υ
DLNA		Υ
Game Mode		Υ
Trilingual Menu (English/Spanish/French)		Υ
Built-In Closed Caption Decoder		Υ
1 0 110 7		Υ
GENERAL		
Power Supply		AC 110 – 127 V, 60 Hz
On Mode Average Power Consumption		52 W
Receiving System		ATSC/ QAM/ NTSC
Dimensions with stand	Height [in (mm)]	20.9" (531 mm)
	Width [in (mm)]	30.7" (779 mm)
Discouries without should	Depth [in (mm)]	8.2" (207 mm)
Dimensions without stand	Height [in (mm)]	19.6" (497 mm)
	Width [in (mm)]	30.7" (779 mm)
Maca Waight with stand files (kg)	Depth [in (mm)]	3.4" (85 mm)
Mass Weight with stand [lbs (kg)] Mass Weight without stand [lbs (kg)]		22.1 lbs. (10.0 kg) 19.9 lbs. (9.0 kg)
Swivel Angle		19.9 lbs. (9.0 kg)
· ·		_
		- Y
Carton Dimensions	Height [in (mm)]	23.1" (585 mm)
	Width [in (mm)]	38.6" (979 mm)
		processor and the second of th
		7.6" (192 mm)
Gross Weight (libs (kg))	Depth [in (mm)]	7.6" (192 mm) 28.7 lbs. (13.0 kg)
Gross Weight [lbs (kg)] Optional Wall-mounting Bracket Model Numbers		7.6" (192 mm) 28.7 lbs. (13.0 kg) TY-WK3L2RW

