

AKAI

AKAI ELECTRIC COMPANY JAPAN

42" Wide-Screen LCD TV

LCT4285TA

Home theater experiences defined by AKAI technology

Product styled for you, performance to enrich your life. Whether your application is simple or demanding, Akai technology will support your lifestyle.

Designed for your life

- Built-in ATSC Tuner for over-the-air HDTV broadcast reception
- High Definition Monitor with 480p, 720p, and 1080i input capability
- High brightness (500 cd/m²)
- 1,366 x 768 native resolution
- Beautiful color depth with a contrast ratio of 400:1
- Wide Screen aspect ratio (16:9) for complete home theater experiences
- 3:2 pull down for optimum movie viewing
- Wide viewing angle (176 degrees H, 176 degrees V)
- Powerful Stereo Sound, 14 watts (7 watts x 2)
- Full-function Remote Control included

Contemporary design for any room

- Elegant design fits any decor

Compatible with a wide range of multi-media components

- HDTV compatible through HDMI and Component (YPbPr) inputs
- Conventional video through S-video and composite video inputs
- VGA port provided for connection to computer



AKAI

TECHNOLOGY & IMAGINATION

* Product's specifications subject to change.
www.akaiusa.com

AKAI

AKAI ELECTRIC COMPANY JAPAN

42" Wide-Screen LCD TV

LCT4285TA

SPECIFICATION

LCD Panel

Screen Size:	42 inch
Aspect Ratio:	16:9
Resolution:	1,366(H) x 768(V)
Contrast:	400:1
Brightness:	500 cd/m ²
Display Color:	16.7M
Response Time:	8 ms
Viewing Angle	
Vertical:	176°
Horizontal:	176°

TV/Video

Tuner:	ATSC/NTSC Tuner
Color System:	NTSC-M
Stereo System:	MTS Stereo Reception
HD Ready:	Yes
Progressive Scan:	Yes
De-interlace:	Yes
3:2 Pull down:	Yes
Comb Filter:	2D
OSD Language:	English, French, Spanish
Audio Output:	7W x 2 Stereo
V-Chip Parental Control:	Yes
Closed Caption Decoder:	Yes

Terminals

VHF/UHF Antenna:	RF Connector x1
Composite Video Input:	RCA x 1set
S-Video Input:	Mini Din 4 Pin x 1
Component Video Input (YPbPr/YCbCr):	RCA x2sets (Auto-Detect 480i/480p/720p/1080i)
HDMI (with HDCP) Input:	HDMI Connector x1
Audio Input:	RCA x4sets
DVI Audio Input:	RCA x1set
VGA Input:	D-Sub 15-pin x1
PC Audio Input:	Stereo Mini Jack x1
Audio Output:	RCA x1set

General

Power Source:	AC 100 - 240V, 50/60Hz
Power Consumption:	250W