

LCTV-26X



26" WXGA Display

- 800:1 Contrast Ratio
- 550 cd/m2 Brightness
- Native 1366 x 768 Resolution
- Video-on-Graphics Capable
- Variable Aspect Ratio Control
- Network Ready RS-232 and RJ-45 Inputs

LCTV-32X



32" WXGA Display

- 800:1 Contrast Ratio
- 550 cd/m2 Brightness
- Native 1366 x 768 Resolution
- Video-on-Graphics Capable
- Variable Aspect Ratio Control
- Network Ready RS-232 and RJ-45 Inputs

Display

Screen Size:	26" Diagonal
Aspect Ratio:	16:9
Resolution:	1366 X 768 WXGA (NI) Multi-scanning PC/MAC, monitor support to 1280 x 1024
Pixel Pitch:	0.4215 mm (H&V)
Contrast Ratio:	800:1
Brightness:	500 cd/m ²
Displayable Colors:	16.7 million
Viewing Angle:	170 degrees
Response:	25 ms

Screen Size:	32" Diagonal
Aspect Ratio:	16:9
Resolution:	1366 X 768 WXGA (NI) Multi-scanning PC/MAC, monitor support to 1280 x 1024
Pixel Pitch:	0.4215 mm (H&V)
Contrast Ratio:	800:1
Brightness:	500 cd/m ²
Displayable Colors:	16.7 million
Viewing Angle:	170 degrees
Response:	25 ms

Connections

Computer Inputs:	(1) DVI-D 24 pin (1) HD-15 pin
Video/HDTV Inputs:	Automatic signal detection for all sources 480i, 480p, 720p, 1080i support (1) Composite Video (RCA-pin) (1) S-Video (9-pin) (1) Component Video (C,Cb,Cr)
Tuner:	(1)TV Tuner (RF),181 Channel
Audio Input:	(6) RCA-pin Type (L/R)
Audio Output:	(1) RCA-pin Type (L/R)
Network Control:	(1) RS232 D-sub 9-pin , (1) RJ45

Computer Inputs:	(1) DVI-D 24 pin (1) HD-15 pin
Video/HDTV Inputs:	Automatic signal detection for all sources 480i, 480p, 720p, 1080i support (1) Composite Video (RCA-pin) (1) S-Video (9-pin) (1) Component Video (C,Cb,Cr)
Tuner:	(1)TV Tuner (RF),181 Channel
Audio Input:	(6) RCA-pin Type (L/R)
Audio Output:	(1) RCA-pin Type (L/R)
Network Control:	(1) RS232 D-sub 9-pin , (1) RJ45

Details

Video:	PIP/POP, Video-on-Graphic, CC
Audio System:	10 W + 10W BTCS Stereo, Surround, MTS/SAP, 4 Spkrs, 5 Langs.
Power Supply:	A/C 100-240V/50-60Hz, DC 12V
Power Usage:	160 W Maximum, 5 W save mode
Other Functions:	Video On Graphics, 3D digital comb filter, 3:2 Pull Down, Digital Zoom, Discreet power on/off, Bass extension circuitry-subwoofer out, V-Chip, CC, Adaptive Motion De-Interlacing, Advanced Video Scaling Selectable Variable/Fixed Audio Out, Surround Sound Processing, Front Panel Lock, Sleep Timer, Static IP Address configuration.
Accessories:	Table Stand, remote, VGA cable, power included
Regulatory:	FCC, UL, CE, BSMI

Video:	PIP/POP, Video-on-Graphic, CC
Audio System:	10 W + 10W BTCS Stereo, Surround, MTS/SAP, 4 Spkrs, 5 Langs.
Power Supply:	A/C 100-240V/50-60Hz, DC 12V
Power Usage:	185 W Maximum, 5 W save mode
Other Functions:	Video On Graphics, 3D digital comb filter, 3:2 Pull Down, Digital Zoom, Discreet power on/off, Bass extension circuitry-subwoofer out, V-Chip, CC, Adaptive Motion De-Interlacing, Advanced Video Scaling Selectable Variable/Fixed Audio Out, Surround Sound Processing, Front Panel Lock, Sleep Timer, Static IP Address configuration.
Accessories:	Table Stand, remote, VGA cable, power included
Regulatory:	FCC, UL, CE, BSMI

Warranty



Rapid Exchange Service

In addition to our standard one year parts and labor limited warranty for LCTV models, an optional one year of our Rapid Exchange Service (RES) is available. With one call, RES either repairs or replaces your out of service monitor within 48 hours to prevent lengthy service interruption.

Share Your Vision

2591 Kerner Blvd., San Rafael, CA 94901
Tel: 415-259-2820 | Fax: 415-259-2828

Toll Free: 800-440-6388
www.net-tv.net