

Norcent

42" Plasma Television

PT-4231



The visual excitement of Plasma television – at an affordable price.

www.norcent.net

There is a difference...

Norcent

PT-4231 42" Plasma Television



Product Features

- 42 inch Widescreen (16:9) plasma TV with high resolution(852 x 480), brightness (700 cd/m²) and contrast (1000:1) for a superior viewing experience
- Built-In NTSC Tuner, compatible with major Digital TV signals (1080i, 720p, 480p and 480i)
- DVI, component, S-video & composite inputs & D-sub for PC connectivity
- Picture-in-picture lets you watch two different sources at the same time
- Built-in speakers with life-like BBE high-fidelity surround sound

Product Specifications

Screen Dimension	42-inch (Diagonal)
Aspect Ratio	16 : 9
Resolution	852 (H) 480 (V) pixels
Pixel Pitch	1.08 (H) 1.08(V) mm
Displayable Color	256 levels, 16.77M colors
Brightness	700cd/
Contrast Ratio (Dark)	1000:1
Viewing Angle	Over 160;
Screen Function	PIP (Enlargeable, Moveable), POP, (R-L, Up-Low)

Signals

Synchronization Range	H: 31 to 69 kHz, V: 50 to 85 Hz
Compatible System	VGA; SVGA; Wide VGA; XGA; SXGA, Text Mode
Input Signals	RGB; NTSC; PAL;
Mini D-sub 15 pin	X
DVI D 29 pin	X
RS232C D-sub 9 pin	X

Input/Output

Component Video (YCbCr)	X
S-Video	X
DTV Component (YPbPr)	X
Composite Video Output	X
Composite Video Input	X
Audio Input RCA Pin Jack x 2	500m Vrms/more than 22k
Audio Output RCA Pin Jack x 1	500m Vrms/more than 22k
Internal Speakers	5W + 5W
External Speakers (Optional)	10W + 10W
Power Supply	AC120V/AC240V 50/60Hz
Power Consumption	300W (typical)

Dimension	1,038 (W) x 640 (H) x 89 (D) mm, 41.3" (W) x 25.5" (H) x 3.5" (D) inches
Weight	34kg/75Lbs 34.5kg/75.9Lbs
Operating Temperature	0 ~ 40 / 32 ~ 104
Operating Humidity	20 ~ 80% (no condensation)
Accessories	Power Cable; VGA Cable (Mini D-sub, 15 pin to Mini D-sub 15 pin Connector); RCA Cable;
	Remote Control w/ Two AA Battery; User Manual
Other Features	3D motion adaptive Scan Converter, with 2-2(50Hz) 2-3 (60Hz) Pull Down, Converter
Regulatory Compliance	Digital Zoom function; Color Temperature Selection; Power Management; Plug and Play (DDC2B) UL; FCC Class B; CE

There is a difference...

www.norcent.net