

Power Consumption:

Runco® PlasmaWall™ XP-OPAL50 DHD Plasma

Runco's XP-OPAL50 DHD is a 50-inch display that combines Runco's proprietary OPAL™ enhancement technology and legendary DHD™ Controller/Processor. The result is flawless video that creates an amazing experience.

Native Resolution:	1920 x 1080	
Screen Size:	50.26 in. (diagonal)	
Screen Aspect Ratio:	16:9	
Image Area (W x H inches)	43.5 x 24.5	
Contrast Ratio:	30,000:1 maximum	
ISF Settings:	Yes	
Inputs (from DHD Controller):	See DHD controller specs below	

Operating Environment: 32°- 104° F (0°- 40°C), 20–80% Humidity (non-condensing)

Altitude = up to 9,100 feet (2,800m)

650 W (.1 watts in standby), maximum

Dimensions (w/o stand): Width: 48.8 in. (1239.5 mm); Depth: 4 in. (101.6 mm); Height: 29.6 in.

(751.8 mm); Weight: 93 lbs. (42 kg)

Regulatory Approvals: FCC Class B, CE, C-Tick

Limited Warranty: Two years parts and labor from the date of delivery to the end user.

RuncoCare[™] and Runco RedCarpet[™] plans are also available.

The XP-OPAL50 DHD ships with: Power cords (US, EU), remote control and two batteries (AAA), warranty

information and registration card, owner's operating manual, cable ties.

Runco DHD Controller Specifications

Aspect Ratios:	4:3, 16:9, Letterbox, VirtualWide™, Native, VirtualCinema™ and Cinema	
Video Processing:	ViVix III™ 1080p output	
Video Standards:	NTSC, PAL, ATSC and SECAM	
Supported Signal Timings:	1080p (23.98, 24, 50, 59.94, 60), 1080i (50, 50 Australia, 59.94, 60), 720p (23.98,	
	24, 25, 29.97, 30, 50, 60), 576p/i, 480p/i, SCART RGB, standard PC timings	
Output:	(1) HDMI v1.3 w/ HDCP and Deep Color up to 12 bits/channel; (1) RJ-11 for	
	display control; (1) RJ-11 for display control	
Inputs:	(1) Composite; (2) S-Video; (1) Component; (2) HD - R (Pr), G (Y), B (Pb), H, V;	
	(2) HDMI v1.3 w/HDCP and Deep Color up to 12 bits/channel	
Communications Control Ports:	Discrete infrared remote, (1) RS-232 9 pin connector; front panel	
Screen Trigger/ Masking Output:	(3) +12 VDC, each rated at 250 mA with over-current protection	
Power Requirements:	100-240V AC (auto sensing) 50/60 Hz, 40W	
Dimensions:	Width: 17 1/2 in. (444.50 mm); Depth: 11 3/16 in. (284.10 mm);	
	Height:3 3/4 in. (95.25 mm), Weight: 13 lbs. (5.9 kg)	
Included Accessories:	Runco remote, batteries, RJ-11 cable and RS-232 adapter, rack mount brackets	
Features:	Highly-compatible with today's video sources, fully-compliant HDMI/HDCP	
	repeater, full ISF™ calibration controls, easy firmware upgrades via USB or	
	serial, customizable splash screen and side-curtain colors	
BRiC Tool:	Backup, Recovery and Clone tool for ease of saving, restoring or cloning	
	calibrations settings	