



RUNCO® CRYSTALSERIES™ CX-OPAL42 LCD

The Runco Crystal Series CX-OPAL42 LCD display with Optical Path Alignment (OPAL) technology is perfect for those who demand stellar image performance with the absolute latest features and elegant design.



Crystal Series LCD Specifications

Native Resolution:	1920 x 1080
Screen Size:	CX-42HD/CX-OPAL42 = 42 in. (diagonal)
Screen Aspect Ratio:	16:9
Available Aspect Ratios:	4:3, Letterbox, 16:9, VirtualWide™
DTV Compatibility:	480i/p, 576i/p, 720p, 1080i, 1080p
ISF Settings:	Yes
Contrast Ratio:	CX-42HD/CX-OPAL42 = 4000:1
Data/Graphics Compatibility:	Refer to Table 7-2
Response Time (typical):	4.5 milliseconds
Vivix Processing:	3:2 or 2:2 pull down
Video/Audio Inputs:	Multiple input combinations with up to (2) Composite Video (1) S-Video (2) Component Video (4) HDMI 1.3a w/HDCP (1) RGB (15-pin D-sub) (5) Analog Audio (4 stereo RCA pairs + 3.5-mm stereo mini jack)
Control Inputs:	(1) RS-232 (9-pin D-sub) (1) Wired IR (3.5-mm mono mini jack)
Outputs:	(1) Digital Audio (S/PDIF optical) (1) Stereo Speakers
Audio System:	10W RMS x 2 Stereo Amplifier
Discrete IR Control:	Source, power and aspect ratios
Power Requirements:	100 to 240 VAC, 50/60Hz

For more information visit www.Runco.com or call 800-237-8626 or +1-503-748-1100.

Specifications are subject to change without notice. ©Copyright 2010 Runco International Inc. All rights reserved.



RUNCO® CRYSTALSERIES™ CX-OPAL42 LCD

The Runco Crystal Series CX-OPAL42 LCD display with Optical Path ALignment (OPAL) technology is perfect for those who demand stellar image performance with the absolute latest features and elegant design.



Crystal Series LCD Specifications

Power Consumption (typical):	CX-42HD/CX-OPAL42 = 130 watts (443.7 BTUs/hour); 5 watts in standby mode
Operating Environment:	40°F to 95°F (5°C to 35°C); 20% to 80% humidity (non-condensing); Altitude = 9,842 feet (3,000 meters)
Dimensions:	CX-42HD/CX-OPAL42 = see Figure 7-1 and Figure 7-2
Weight (including stand):	CX-42HD/CX-OPAL42 = 77.2 lbs. (35.00 kg)
Regulatory Approvals:	Complies with UL, FCC, CE, RoHS, C-Tick, NOM, GOST
Limited Warranty:	Two (2) years parts and labor from the date of delivery to the end user.

For more information visit www.Runco.com or call 800-237-8626 or +1-503-748-1100.

Specifications are subject to change without notice. ©Copyright 2010 Runco International Inc. All rights reserved.