

RUNCO® VISTAGE™

V-58HD



| | |
|------------------------------|---|
| Native Resolution: | 1920 x 1080 (1080p) |
| Diagonal Size: | 58" |
| Screen Aspect Ratio: | 16:9 (1.76:1) |
| Available Aspect Ratios: | 4:3, 16:9, Letterbox, VirtualWide™ |
| Square Inches: | 1438 sq inches |
| Active Area: | 58.02" |
| DTV Compatibility: | 480i, 480p, 576i, 576p, 720p, 1080i, 1080p (24, 50, 60Hz) |
| Contrast Ratio (sequential): | 1,000,000:1 typical, 10,000:1 minimum |
| ISF Settings: | Yes |
| Date/Graphics Compatibility: | Up to 1920 x 1200 |
| Inputs: | See DHD Specifications |
| Outputs: | (2) HDMI 1.3 w/HDCP/CEC/audio, Speaker |
| Power Requirements: | 100-240V AC, 50/60Hz |
| Power Consumption: | 550 W (1 Watt standby) |
| Operating Environment: | 32°- 104° F (0°- 40°C), 20–80% Humidity (non-condensing) |
| Altitude: | Up to 9,100 feet (2,800m) |
| Dimensions: | Width: 56.81" (1442.94mm) |
| (without stand) | Height: 34.68" (880.98mm) |
| | Depth: 1.70" (43.26mm) |
| Weight: | 105lbs |
| Optional Speaker Bar: | Slim design, 2 channel audio bar with integrated design (attaches to display for table stand installation or to wall) |
| Optional Mounts: | Halo-style table stand and VESA-compatible wall mount |
| Regulatory: | FCC Class B, CE, C-Tick |
| Design by Runco™ options: | FinishPalette™ on optional veil accessory and halo table stand, ColourPalette™, FrameGallery™ |
| Limited Warranty: | Two years parts and labor from the date of shipment from Runco. Extended RuncoCare™, Runco RedCarpet™, and PremierCare™ plans are also available. |

For more information visit www.Runco.com or call 800-237-8626 or +1-503-748-1100.



Runco DHD-LS Controller Specifications:

| | |
|------------------------------|--|
| Aspect Ratios: | 4:3, 16:9, Letterbox, VirtualWide™, Cinema, Virtual Cinema™, Native |
| Video Standards: | HDMI and DVI with HDCP for digital video, Component and RGB HDTV (1080p, 1080i, 720p), Component and RGB EDTV (576p, 480p), Component and Composite SDTV (576i, 480i), RGB SCART with adaptor, NTSC (M, 4.43), PAL (B, G, H, I, N, M), SECAM (M) |
| Inputs: | (4) HDMI 1.4 with CEC and Deep Color; (1) Component/SCART (3 x RCA); (2) Component/RGBHV (5 x BNC); (3) Composite |
| Output: | (1) HDMI 1.4 with CEC and Deep Color to display; (1) HDMI 1.4 with Deep Color to second display or audio processor |
| Display Communication: | HDMI via RuncoLink™ |
| Communication Control Ports: | (1) RS-232 (female DB9) for serial commands and firmware upgrade; Discrete infrared remote |
| Ethernet Communication: | (1) RJ45 (female) for web server, e-mail, auto firmware upgrade and Telnet |
| Power Requirements: | 100 – 240V AC (auto-sensing), 50/60 Hz, 30 watts (typical) |
| Operating Environment: | 50°F to 104°F (10°C to 40°C), 0% to 85% humidity (non-condensing), up to 10,000' altitude |
| Dimensions: | Length = 16.97 inches (431.04 mm) ; Width = 9.76 inches (247.90 mm); Height = 1.65 inches (41.91 mm); Weight: 8 pounds |
| Accessory Applications: | Runco Firmware Upgrader, Runco BRiC (backup, restore, clone), CalMAN by SpectraCal for automatic calibration |
| Regulatory Approvals: | cTUVus, FCC class B, CE, RoHS, China RoHS, WEEE, C-Tick, CCC, local conformances as required |
| Limited Warranty: | (2) Two years parts and labor from the date of shipment from Runco |