



LME-37X8

37" HD-Ready LCD Display



Features

Video Processing

- MotionDSC™ Video Processor
- 3:2 Pull-Down
- Adaptive Motion De-interlacing
- Edge Smoothing
- IIS Intelligent Image Scaling Engine
- Digital Comb Filter

Convenience

- Variable Aspect Ratio Control
- Picture-in-Picture
- Side by side Picture
- Preset Temperature Setting
- Quick Access Menu
- Auto Video Detection
- Video Last Memory
- Sleep Timer
- Power Save
- Closed Captioning
- V-chip Parental Control

Remote Management Console

- Selectable RJ-45/RS-232 Control
- Software Support for RS-232
- Ethernet Web-Based Console
- Static IP Configuration

Model Number		LME-37X8
Screen Size		37" Diagonal
Aspect Ratio		16:9
Number of Pixels		1366 x 768
Contrast Ratio		1000:1
Brightness		500 cd/m ²
Displayable Colors		16.77 Million Colors
Viewing Angle		176 degree
Response Time (Gray to Gray)		8 ms
Video Signal Compatibility		480i, 480p, 720p, 1080i
Display Type		TFT-LCD
Tuner		NTSC
Connectivity		
DVI Input	DVI-D 24 pin x 1	
RGB Input	D-Sub 15-pin x 1	
RF Connector	RF 181CH x 1	
Composite/S-Video Input	RCA-pin x 2	
RS-232	D-Sub 9-pin x 1	
RJ-45	RJ-45 x 1	
Component Video Input	RCA-pin x 2 (Y/CB/CR, Y/PB/PR)	
Audio Input	RCA-pin (L/R) x 6	
RGB Output	D-Sub 15-pin x 1	
Audio Output	RCA-pin (L/R) x 1	
Subwoofer Output	RCA-pin Type x 1	
Power Supply	100V~240V/50~60Hz	
Power Consumption	210W/2.0A	
Dimensions	with stand	37" x 37 3/4" x 8 3/4"
	without stand	37" x 25 7/8" x 4 3/4"
Weight	with stand	49.6 lbs
	without stand	46.3 lbs
Audio	Integrated Bottom Speakers 10 W X 2	
Optional Accessory		
Wall Mount Bracket		Horizontal Tilt Mount

