

<b>Model Number: SC323FI</b>		<b>Features</b>	
UPC Code	859259002569	Built in 3D PAL/NTSC Comb Filter	
<b>Display Features</b>		Built in 3D Video Noise Reduction	
Screen Size	32"	Built in BTSC/SAP	
Active Area	698mm(H)×392mm(V)	Over-The-Air ATSC/NTSC RF Input Support	
Aspect Ratio	16:09	Clear-QAM Digital Cable Support	
Panel Resolution	1366×768	Digital/Analog Channel auto tuning	
Panel Refresh Rate	60Hz	Support V-CHIP/CCD/Favorite Channel Edition	
Brightness	450 cd/m2 (Typical)	HD compatible :480I,576I,480P,576P,720P,1080I	
Dynamic Contrast ratio	4000:1 (Typical)	USB Supports File Format: Service only	
Viewing Angle	±178°	OSD Language: English/French/Spanish	
Dot Pitch	0.51075(H)×0.51075(V)	<b>Accessories Included</b>	
Maximum Color	16.7 Million (8-Bit)	Remote Control / Battery Included	
Response time Gray-Gray	10ms	Owners Manual / Quick Start Guide / HDMI Cable	
<b>Electronics</b>		<b>Power Requirements</b>	
Scaler Solution	MSD318	Power Source	AC100-240V 50/60Hz
DNR	3D	Power ON consumption	<110W
Digital Comb Filter / Type	3D	Standby consumption	<0.7W
<b>TV System &amp; Video Standards Supported</b>		Operating Temperature	5°C-35°C
TV System	ATSC/NTSC M	Operating Humidity	20%-80%
Channel CATV - UHF/VHF (ATV)	181 channel	<b>Dimension (WxHxD)</b>	
Composite / S-Video input	PAL/NTSC	Unit w/ Stand	31.3" X9.2"X22"
<b>Video Connections</b>		Unit w/o Stand	31.3"X3.8"X20.3"
Analog&Digital TV Tuner	×1	Carton	34.2"X6.7"X24.4"
Composite Video Input	×2	<b>Weight (LBS)</b>	
S-Video Input (4pin DIN)	×1	Net Weight w/Stand	23.32
Component Input (Y,Cb,Cr/Y,Pb,Pr)	×2	Net Weight w/o Stand	20.24
VGA Input (15 pin D-Sub)	×1	Gross Weight	27.94
DVI-D / DVI-I Input	NO	<b>Warranty &amp; Support</b>	
HDMI Input	×3	One Year Manufacture Warranty	
USB	service	Toll Free Customer Support	
<b>Audio</b>		On-Line Manual / Firmware Access	
Maximum Audio Output	2×8W	<b>Logistic</b>	
Number of speakers	×2	Standard Pallet Unit Load	
Audio Surround	NO	20GP' Container Unit Load w/o Pallet	258pcs
<b>Audio Connections</b>		40GP' Container Unit Load w/o Pallet	531pcs
Stereo Mini Phono Jack Input (3.5mm)	×1(VGA Audio)	40HQ' Container Unit Load w/o Pallet	708pcs
RCA Input	×4(R/L)		
Headphone: Stereo Mini (3.5mm)	NO		
RCA Output	NO		
Coax Digital Output	×1		
<b>VGA Resolutions Supported</b>			
640x480, 800x600, 1024x768, 1360x768			