

TF-TV3209

32" TFT LCD TV with INTEGRATED HDTV TUNER

- 32" Flat Screen TFT LCD Panel
- Widescreen 16:9 Aspect Ratio
- 1366 x 768 Resolution
- Integrated HDTV Tuner (ATSC/NTSC)
- Multiple Input Connections
- Integrated 3-way Stereo Speakers
- V-Chip Parental Control
- Convenient On-screen Display
- Desktop or Wall-Mountable Design

Accessories Included

- Full Function Remote Control
- A/V Cable

Carton - Inner: 1 Master: 1
UPC: 7 16829 99329 3

SPECIFICATIONS

Power	Voltage	AC 100V to 240V, 50/60Hz	
Consumption	Operation mode	127W	
	Power Saving Mode	Under 3W	
Panel	Aspect Ratio	16:9	
	Resolution	1366*768	
	Pixel Pitch	0.170mm*0.511mm	
	Number of color	16.7M Color	
	Brightness	500cd/m ²	
	Contrast Ratio	1600:1	
	Viewing Angle	R/L(176), U/D(176)	
	Pixel Response Time	8MB	
Input Terminal	Front & Side	7 Keys (power,source select,vol up/down, ch up/down, menu)& IR input	
	Rear	Antenna <ATSC/NTSC>	1
		AV	2
		S-Video	1
		component video	2
		PC Input (D-Sub 15pin) with Audio	1
		HDMI	1
		RS-232C (only service)	1
		AC Power	1
		Digital Audio (Optical)	1
Output Terminal		Rear	Digital Audio (Optical)
Input Source	PC (Analog RGB)	VGA, SVGA, XGA, HDTV(480p~1080i) Max. Input Resolution - 1024 x 768/60Hz	
	AV Input	HDTV : ATSC TV : NTSC-M AV : NTSC-M S-Video Jack , Sound (L,R) Component1 Video (480i ~1080i), Sound (L,R) Component2 Video (480i ~1080i), Sound (L,R)	
Output Source	Output	Audio stereo Audio Dolby 5.1	
Weight (LBS)	Gross	58.4	
	Net	55.1	
Box Size	Gross	37.4"W x 291.1"H x 11.0"D	
	Net	31.9"W x 25.3"H x 4.1"D	
Sound	Audio Mode	Standard/Music/Film/Speech/Custom	
	Stereo	AVL, MTS (Mono,Stereo, Dual Languages)	
	Sound effect	Dolby Digital	
	Sound Output	10W x 2	
	Impedance	8Ω(L) + 8Ω(R)	
Special Features	Signal	10 bit Video signal LVDS	
	OSD	Korean / English /Spanish	
	Aspect Mode	Wide,Panorama, Zoom, 4:3, 16:9	
	Picture mode	Dynamic, Standard, Movie, Sports, PC, Custom	
	Custom Adjustment	Brightness, Contrast, Sharpness, Color, Tint etc.	
	Color Tone	Cool / Normal / Warm	
	Sleep timer	10 ~ 180 minutes	
	PC resolution	Max. Input Resolution - 1024 x 768/60Hz	
	V-Chip, CC	Yes	
	Filter	3D digital comb filter/2D Comb Filter	
	Noise	Digital noise reduction	
	Wall Mounting	VESA-200	
	Others	Digital EPG	
			Full Function Remote Controller
	Operating Condition	Operating Temperature	0~50 degree
	Operating Humidity	80% Max.(non-condensina)	
	Storage Temperature	-20~70 degree	
Certification	UL, FCC, TÜV, UL		



Designed and Manufactured in South Korea

HDTV

HDMI
High-Definition Multimedia Interface

COBY®

www.cobyusa.com and www.ecoby.com

©2006 COBY ELECTRONICS CORPORATION Features and specifications are subject to change without prior notification Printed in USA