

**TPT5000HD**  
**Product Specifications**



Model TPT5000HD

Model TPT5000HD					
LCD Panel	Display Size	50"	Inputs	RF (DTV)	75 ohm F-Type x 1
	Response Time	8 ms		Composite	RCA x 2
	Aspect Ratio	16:9		S-Video	Y/C x 1
	Resolution	1366 x 768 (WXGA)		Component	RCA x 2
	Color	8 bit, 16.77 M		HDMI	x 1
	Brightness	1500 cd/m <sup>2</sup>		DVI-D	x 1
	Contrast Ratio	5000:1		PC	D-Sub x 1
	Viewing Angle	U/D: 88/88, R/L: 88/88		RS-232C	x 1 (rear)
	TV Signal	ATSC/NTSC	Audio	PC/DVI x 1, Component/S-Video/AV x 2	
System	Tuner	181 Ch FS Tuner	Misc	Picture	PIP, POP
	AV Signal	NTSC		Picture Swap	o
	Text	Closed Caption/V-Chip		Picture Shift	o (PIP)
	PSM	Dynamic, Standard, Mild, Game, User		Sleep Timer	10~240 min
Video	Picture Mode	16:9, 4:3, Panorama, Zoom		On/Off Timer	o
	Color Status Memory	o		Clock	o
	Progressive Scan	o		OSC	English, French, German, Spanish, Italian
	Filter	3D Comb Filter		Net (lb)	84 (Display)
Sound	Sound System	SPDIF Digital Sound Out, HDMI 125 Digital Sound Support	Weight	Gross (lb)	93 (Display)
	Sound Output	10W + 10W, 8 ohm		Dimension	Set size (WxDxH, Inch)
	SSM	Flat, Music, Movie, Speech, User	With Stand and Speaker		
	Surround	o	58.54 x 3.94 x 29.06		
	Speaker	External Speaker Output	Without Stand		
Power	Consumption	300W			
	Standby	4W			