

# 2011 VIERA® VT30 Series Plasma



Screen image simulated.

Available Models:  
TC-P55VT30  
TC-P65VT30

## FULL HD 3D (1 PAIR OF GLASSES INCLUDED)

Revolutionary VIERA Full HD 3D Technology with high-precision shutter control eyewear delivers award-winning realism that immerses you in the image.



TY-EW3D2M

## ONE SHEET OF GLASS DESIGN

A sleek, frameless look that will enhance any décor.

## INFINITE BLACK PRO 2 PANEL

Delivers deep, rich blacks and high contrast in virtually any viewing area, from living rooms to bedrooms.

## VIERA CONNECT™ WI-FI READY

Enjoy a world of movies, sports and other online apps, plus Skype™ video calls on your VIERA HDTV.

- THX
- Motion Smoother
- Fast Switching Phosphors
- 600 Hz Sub-field Drive
- 1080p Full HD Resolution
- 2D/3D Conversion
- Game Mode
- 24p Cinematic Playback
- ISFccc
- Skype™ Video Calling\*
- VIERA Image Viewer H.264 with 3D playback (Movie and Photo capable)
- DLNA
- VIERA Link™
- PC Input
- 4 HDMI
- 3 USB
- RS232c Terminal
- Mercury and Lead-Free Panel
- Long Panel Life (up to 100,000 Hours)



**Panasonic**  
ideas for life

**VIERA**

\*Compatible HD web camera and Internet connection required for Skype™ video calls.

# 2011 VIERA®

## VT30 Series Plasma

		TC-P65VT30	TC-P55VT30
<b>VIDEO</b>			
Screen Size Diagonal (in)		64.7	55.1
Aspect Ratio		16:9	16:9
Number of Pixels		2,073,600 (1,920 x 1,080)	2,073,600 (1,920 x 1,080)
Moving Picture Resolution		1,080 lines	1,080 lines
Shades of Gradation		6,144 equivalent	6,144 equivalent
HDTV Display Capability (1080p, 1080i, 720p)		Y	Y
EDTV Display Capability (480p)		Y	Y
Aspect Control		4:3, ZOOM, FULL, JUST, H-FILL FOR TV/AV MODES 4:3, FULL FOR PC MODE	4:3, ZOOM, FULL, JUST, H-FILL FOR TV/AV MODES 4:3, FULL FOR PC MODE
Louver Filter		Y	Y
600 Hz Sub-field Drive		Y	Y
24p Cinematic Playback		Y	Y
24p Playback (2 : 3)		Y	Y
Deep Color		Y	Y
x.v.Color		Y	Y
THX Mode		Y (3D/2D)	Y (3D/2D)
ISFccc		Y	Y
Pro Setting		Y	Y
Super Resolution		Y	Y
3D Color Management		Y	Y
Sub Pixel Control		Y	Y
Motion Pattern Noise Reduction		Y	Y
<b>FULL HD 3D</b>			
3D Panel		Y	Y
3D 24p Cinema Smoother		Y	Y
2D-3D Conversion		Y	Y
3D Image Viewer		Y	Y
3D Active Shutter Eyewear		1 included	1 included
<b>AUDIO</b>			
Speakers		Dual Speaker, Woofer	Dual Speaker, Woofer
Number of Speakers		3	3
Audio Output		22 W (6 + 6 + 10)	22 W (6 + 6 + 10)
CONEQ		Y	Y
Surround Sound		Y	Y
<b>JACKS</b>			
Integrated ATSC Tuner		Y	Y
VIERA Image Viewer		Y (AVCHD/ MPEG2/ JPEG/ MP3 playback)	Y (AVCHD/ MPEG2/ JPEG/ MP3 playback)
HDMI	Input	4 (4 side)	4 (4 side)
	Support Feature	Audio Return Channel (Input 1)/ 3D Input (All)	Audio Return Channel (Input 1)/ 3D Input (All)
USB		3	3
Analog Audio Input ( for HDMI/DVI)		Y	Y
Composite Video Input		RCA x 1 (lower)*	RCA x 1 (lower)*
Audio Input (for Video)		—	—
PC Input		D-sub 15-pin x 1 (rear)*	D-sub 15-pin x 1 (rear)*
Component Video Input (Y, PB, PR)		RCA x 1 (lower)*	RCA x 1 (lower)*
Audio Input (for Component Video)		RCA x 1 (lower)*	RCA x 1 (lower)*
LAN Port		1 (lower)	1 (lower)
RS232C		Dsub 9pin x 1 (lower)*	Dsub 9pin x 1(lower)*
Digital Audio Output (Optical)		1*	1*
<b>CONVENIENCE</b>			
VIERA Link		Y	Y
VIERA Connect (IPTV)		Y	Y
Easy IPTV		—	—
Wireless LAN Adaptor		Y	Y
VIERA Tools		Y	Y
DLNA		Y	Y
Game Mode		Y	Y
Pixel Orbiter (Anti-Image Retention)		Y	Y
Trilingual Menu (English/Spanish/French)		Y	Y
Built-In Closed Caption Decoder		Y	Y
Off-Timers		Y	Y
<b>GENERAL</b>			
Power Supply		AC 120 V, 60 Hz	AC 120 V, 60 Hz
On Mode Average Power Consumption		159W	119W
Receiving System		ATSC/ QAM/ NTSC	ATSC/ QAM/ NTSC
Dimensions with Stand	Height [in (mm)]	39.2" (994 mm)	33.4" (847 mm)
	Width [in (mm)]	61.9" (1,570 mm)	52.4" (1,329 mm)
	Depth [in (mm)]	15.8" (400 mm)	15.3" (387 mm)
Dimensions without stand	Height [in (mm)]	37.7" (956 mm)	31.9" (810 mm)
	Width [in (mm)]	61.9" (1,570 mm)	52.4" (1,329 mm)
	Depth [in (mm)]	Speaker depth: 2.4" (60 mm); Panel depth: 1.6" (39 mm)	Speaker depth: 2.2" (55 mm); Panel depth: 1.5" (37 mm)
Weight with stand [lbs (kg)]		138.9 lbs. (63.0 kg)	98.2 lbs. (44.5 kg)
Weight without stand [lbs (kg)]		123.5 lbs. (56.0 kg)	84.9 lbs. (38.5 kg)
Operating Temperature		32°F – 104°F (0°C – 40°C)	32°F – 104°F (0°C – 40°C)
Safety Standard		UL60065 (7th edition)/ C-UL	UL60065 (7th edition)/ C-UL
Carton Dimensions	Height [in (mm)]	46.9" (1,191 mm)	36.8" (933 mm)
	Width [in (mm)]	67.7" (1,719 mm)	58.7" (1,490 mm)
	Depth [in (mm)]	14.9" (377 mm)	12.1" (307 mm)
Gross Weight [lbs (kg)]		167.6 lbs. (76.0 kg)	116.9 lbs. (53.0 kg)
Swivel Angle		—	—
One-Sheet-of-Glass Design		Y	Y
Optional Wall-mounting Bracket Model Numbers		TY-WK6P1RW	TY-WK5P1RW

\*with Special Adapter Cable (dedicated)