





## Plasma Display Panel Model P50A

### Key Features

- 50 Inch display
- 1365 x 768 resolution
- Enhanced Picture-In-Picture
- Outstanding image processing
- Built-in stereo amplifier
- Quiet operation
- 700:1 Contrast ratio
- 16:9 aspect ratio
- 160° viewing angle
- Portrait capability



**P50A**  
**DUKANE**

# Plasma Display Panel P50A

Dukane P50A plasma display panel draws your audience right into your message and commands their attention. Super bright images, pure reds and saturated colors combined with built-in stereo amplifier makes sure your message is always loud and clear no matter what your environment or angle. In areas with direct lighting an anti-glare filter keeps images vibrant and contrast high for a perfect image every time.

Advanced scan conversion and 3/2 pull down processing, delivers smooth, lifelike video. A patented color filter ensures realistic color.



Connect to multiple sources from video to HD to RGB. Signal loop-through capability allows a source to easily be looped from one monitor to the next enabling you to connect 4 displays without the use of an external DA\*.

A sleek new design with cable management system, programmable timer and portrait capability make the P50A the perfect choice for any environment.

## Key features:

- 50 Inch display
- 1365 x 768 resolution
- Enhanced Picture-In-Picture
- Outstanding image processing
- Built-in stereo amplifier
- Quiet operation
- 700:1 Contrast ratio
- 16:9 aspect ratio
- 160° viewing angle
- Low power consumption
- Portrait capability
- Cable management
- Programmable timer

\* Signal DA is required for sending a signal to more than 4 monitors simultaneously.

# DUKANE

Dukane Corporation  
Audio Visual Products Division  
2900 Dukane Drive  
St. Charles, Illinois 60174  
800-676-2485 or 2486  
630-584-5156  
avsales@dukcorp.com  
www.dukcorp.com/av



toll-free  
fax  
e-mail

## Specifications P50A

Display, diagonal	50 inches
Display, area	43.5" (H) x 24.5" (V)
Resolution, pixels	1365 (H) x 768 (V), WXGA
Video Compatibility	NTSC, PAL, SECAM, HDTV 1080i, 1035i, 720p, 625i/p, 540p, 525i/p, 480i/p
Aspect Ratio	16:9
Number of Colors	16.7 million
Contrast Ratio	700:1
Brightness	450cd/sq m
Viewing Angle	160 degrees
Image Features	Portrait/Landscape Mode, Zoom, Enhanced PIP
Computer Compatibility	VGA, SVGA, XGA, SXGA, UXGA, WVGA, WXGA
Scanning Frequency	fh 15.5-110 kHz, fv 50-120 Hz
Inputs, Computer	15-pin mini D-sub 5 BNC (RGB/HV) 24-pin DVI-D (HDCP Compatible)
Inputs, Video	Composite BNC x 1 Composite RCA x 1 S-Video 4-pin DIN RCA Component (Y,Pb,Pr/Y,Cb,Cr) BNC Component (Y,Pb,Pr/Y,Cb,Cr)
Inputs, Audio	RCA Stereo x 3
Ouptup, Computer	15 PIN mini D-sub
Output, Video	Composite BNC
Audio	Internal Amplifier, 8W x 2 ouput power
Control	9-pin mini D-Sub, RS232, Wired remote(In/Out)
Operating Temperature	32-104 degrees F (0-40 degrees C) (20-80% operating humidity)
Power	120V 50/60 Hz, 480W (typical), 0.9W (standby)
Weight	96.4 lbs.
Size (W x H x D)	48.1" x 29" x 3.8"
Shipping Weight	125 lbs.
Carton Size	17" x 33" x 53"
Safety	FCC Class A, UL Approved
Accessories Included	Power Cord, User Manual, Remote Contol, Batteries, Cable Clamps
Optional Accessories	Tabletop Stand (PX-ST1U), Attachable Speakers (PX-50SP1U) Terminal Cover (PX-CV1U) Fixed Wall Mount (FWMK) Tilt Wall Mount (TWMK) Ceiling Mount (CMK) Fixed Wall Mount for PC (FWMKPC) Tilt Wall Mount for PC (TWMKPC) Ceiling Mount for PC (CMKPC)

One (1) year limited warranty on parts and labor in North America, lamp excluded (for other locations, local warranties apply).

# TYR