

2013 VIERA® S60 SERIES PLASMA



Screen image simulated.



Available Models:
 TC-P65S60 TC-P50S60
 TC-P60S60 TC-P42S60
 TC-P55S60

SMART TV MADE EASY



Swipe and Share 2.0

Flick a photo or video from your smartphone or tablet straight to your TV.

1080P FULL HDTV

Experience the highest picture quality available for the sharpest images and color.

600HZ SUB-FIELD DRIVE

Enjoy smoother images with less blurring and flare.

ONLINE MOVIES WITH BUILT-IN WIRELESS LAN

Watch your favorite content with wireless connectivity.

- 2 HDMI
- 2 USB
- Media Player (movie and photo-capable)
- Touch Pen Function (touch pen not included)
- VIERA Link™
- Mercury and Lead-free Panel
- Long Panel Life (up to 100,000 hours)



2013 VIERA® S60 SERIES PLASMA

| | | TC-P65S60 | TC-P60S60 | TC-P55S60 | TC-P50S60 | TC-P42S60 | |
|-------------------------------------|---|--|--|--|--|--|--------------------------------|
| PICTURE QUALITY | | | | | | | |
| DISPLAY | Panel | — | — | — | — | — | |
| | Aspect Ratio | 16:9 | 16:9 | 16:9 | 16:9 | 16:9 | |
| | Panel Drive | 600 Hz Sub-field Drive | 600 Hz Sub-field Drive | 600 Hz Sub-field Drive | 600 Hz Sub-field Drive | 600 Hz Sub-field Drive | |
| | Picture Mode | Vivid/Standard/Home Theater/Cinema/Custom | Vivid/Standard/Home Theater/Cinema/Custom | Vivid/Standard/Home Theater/Cinema/Custom | Vivid/Standard/Home Theater/Cinema/Custom | Vivid/Standard/Home Theater/Cinema/Custom | |
| | Contrast | 1,4,000,000 | 1,4,000,000 | 1,4,000,000 | 1,4,000,000 | 1,4,000,000 | |
| | Filter | — | — | — | — | — | |
| | Shades of Gradation | 6,144 gradation steps | 6,144 gradation steps | 6,144 gradation steps | 6,144 gradation steps | 6,144 gradation steps | |
| | 1080 Pure Direct | — | — | — | — | — | |
| | DCI 98% Color Space | — | — | — | — | — | |
| | Super Clear Resolution | — | — | — | — | — | |
| | Dot Noise Reduction | Y | Y | Y | Y | Y | |
| | THX Mode | — | — | — | — | — | |
| | ist Mode | — | — | — | — | — | |
| | 24p Playback (3:2) / 24p Smooth Film | Y/— | Y/— | Y/— | Y/— | Y/— | |
| | Hexa-processing Engine | — | — | — | — | — | |
| 3D | 3D Type | — | — | — | — | — | |
| | 3D 24p Cinema Smoother | — | — | — | — | — | |
| | 2D-3D Conversion | — | — | — | — | — | |
| | 3D Motion Remaster | — | — | — | — | — | |
| | Dedicated 3D Eyewear | — | — | — | — | — | |
| SOUND QUALITY | Speakers | Full Range x 2 | Full Range x 2 | Full Range x 2 | Full Range x 2 | Full Range x 2 | |
| | Speaker Output | 20 W (10 + 10) | 20 W (10 + 10) | 20 W (10 + 10) | 20 W (10 + 10) | 20 W (10 + 10) | |
| | Surround Mode | V-Audio | V-Audio | V-Audio | V-Audio | V-Audio | |
| | — | — | — | — | — | — | |
| EASY OPERATION | | | | | | | |
| | my Home Screen | — | — | — | — | — | |
| | Camera Integrated | — | — | — | — | — | |
| | Voice Interaction | — | — | — | — | — | |
| | Voice Guidance | — | — | — | — | — | |
| | Touchpad Controller | — | — | — | — | — | |
| | Electronic Touch Pen | Y (optional touch pen is required) | Y (optional touch pen is required) | Y (optional touch pen is required) | Y (optional touch pen is required) | Y (optional touch pen is required) | |
| | eHelp | Y | Y | Y | Y | Y | |
| | Product Support Center | — | — | — | — | — | |
| | — | — | — | — | — | — | |
| | — | — | — | — | — | — | |
| NETWORKING | | | | | | | |
| | VIERA Remote2 (smartphone app) | Y | Y | Y | Y | Y | |
| | Swipe and Share2.0 | Y | Y | Y | Y | Y | |
| | Browse and Share | — | — | — | — | — | |
| | Remote Play | — | — | — | — | — | |
| | App Launcher | — | — | — | — | — | |
| | Smart Calibration | — | — | — | — | — | |
| | VIERA Connect | — | — | — | — | — | |
| | Online Movies | Y | Y | Y | Y | Y | |
| | Web Browser | — | — | — | — | — | |
| | Skype on TV | — | — | — | — | — | |
| | Media Player (picture/movie/music) | Y | Y | Y | Y | Y | |
| | Support Format | MKV/MP4/M4v/FLV/3GPP/VR0/VOB/TS/PS, MP3/AAC/FLAC/WAV, JPEG | MKV/MP4/M4v/FLV/3GPP/VR0/VOB/TS/PS, MP3/AAC/FLAC/WAV, JPEG | MKV/MP4/M4v/FLV/3GPP/VR0/VOB/TS/PS, MP3/AAC/FLAC/WAV, JPEG | MKV/MP4/M4v/FLV/3GPP/VR0/VOB/TS/PS, MP3/AAC/FLAC/WAV, JPEG | MKV/MP4/M4v/FLV/3GPP/VR0/VOB/TS/PS, MP3/AAC/FLAC/WAV, JPEG | |
| | DLNA | Y | Y | Y | Y | Y | |
| | Bluetooth® Compatible* | Y (optional: touch pen) | Y (optional: touch pen) | Y (optional: touch pen) | Y (optional: touch pen) | Y (optional: touch pen) | |
| | VIERA Link | Y | Y | Y | Y | Y | |
| Wireless LAN | Y | Y | Y | Y | Y | | |
| ECO | | | | | | | |
| | Eco Navigation | Y | Y | Y | Y | Y | |
| | C.A.T.S. | Y | Y | Y | Y | Y | |
| | Energy Star® | — | — | — | — | — | |
| DESIGN | | | | | | | |
| Design Concept | Narrow Bezel | Narrow Bezel | Narrow Bezel | Narrow Bezel | Narrow Bezel | | |
| TERMINAL | | | | | | | |
| TUNER | Tuner | ATSC/QAM/NTSC | ATSC/QAM/NTSC | ATSC/QAM/NTSC | ATSC/QAM/NTSC | ATSC/QAM/NTSC | |
| | TERMINAL | HDMI Input | 2 (2 rear) | 2 (2 rear) | 2 (2 rear) | 2 (2 rear) | 2 (2 rear) |
| | | Support Feature | Audio Return Channel (Input 2) | Audio Return Channel (Input 2) | Audio Return Channel (Input 2) | Audio Return Channel (Input 2) | Audio Return Channel (Input 2) |
| | Component Video Input Shared with Composite | RCA phono type x 1 (rear) | RCA phono type x 1 (rear) | RCA phono type x 1 (rear) | RCA phono type x 1 (rear) | RCA phono type x 1 (rear) | |
| | USB2.0 | 2 | 2 | 2 | 2 | 2 | |
| | SD Card | — | — | — | — | — | |
| | Ethernet | 1 (rear) | 1 (rear) | 1 (rear) | 1 (rear) | 1 (rear) | |
| | Digital Audio Output (Optical) | 1 (rear) | 1 (rear) | 1 (rear) | 1 (rear) | 1 (rear) | |
| | Headphone Jack | — | — | — | — | — | |
| | Service Port | — | — | — | — | — | |
| GENERAL | | | | | | | |
| Power Supply | AC 120 V, 60 Hz | AC 120 V, 60 Hz | AC 120 V, 60 Hz | AC 120 V, 60 Hz | AC 120 V, 60 Hz | | |
| Screen Size Diagonal (inches) | 64.7 | 60.1 | 55.1 | 49.9 | 41.9 | | |
| On Mode Average Power Consumption | TBD | TBD | TBD | TBD | TBD | | |
| Standby Power Consumption | TBD | TBD | TBD | TBD | TBD | | |
| Off Mode Power Consumption | TBD | TBD | TBD | TBD | TBD | | |
| Display Resolution | 1,920 (W) x 1,080 (H) | 1,920 (W) x 1,080 (H) | 1,920 (W) x 1,080 (H) | 1,920 (W) x 1,080 (H) | 1,920 (W) x 1,080 (H) | | |
| Dimensions (W x H x D) (w/o stand) | 59.1" x 34.6" x 3.2" (General depth: 2.5") | 55.0" x 32.5" x 3.2" (General depth: 2.5") | 50.7" x 30.0" x 3.2" (General depth: 2.5") | 46.2" x 27.5" x 3.2" (General depth: 2.5") | 39.2" x 23.5" x 3.2" (General depth: 2.5") | | |
| Dimensions (W x H x D) (with stand) | 59.1" x 36.9" x 14.2" | 55.0" x 34.6" x 13.2" | 50.7" x 32.2" x 13.2" | 46.2" x 29.6" x 11.7" | 39.2" x 25.6" x 10.1" | | |
| Weight (w/o stand) | 75.0 lbs. | 66.2 lbs. | 57.4 lbs. | 46.3 lbs. | 35.3 lbs. | | |
| Weight (with stand) | 84.9 lbs. | 75.0 lbs. | 66.2 lbs. | 53.0 lbs. | 40.8 lbs. | | |
| Swivel Angle | — | — | — | — | — | | |
| Wall Bracket | TY-WK6P1RW | TY-WK5P1RW | TY-WK5P1RW | TY-WK4P1RW | TY-WK4P1RW | | |
| Operating Temperature | 32°F - 104°F (0°C - 40°C) | 32°F - 104°F (0°C - 40°C) | 32°F - 104°F (0°C - 40°C) | 32°F - 104°F (0°C - 40°C) | 32°F - 104°F (0°C - 40°C) | | |
| Safety Standard | US: UL60065/FCC Parts15; CANADA: CSA C22.2/IC BETS-7 | US: UL60065/FCC Parts15; CANADA: CSA C22.2/IC BETS-7 | US: UL60065/FCC Parts15; CANADA: CSA C22.2/IC BETS-7 | US: UL60065/FCC Parts15; CANADA: CSA C22.2/IC BETS-7 | US: UL60065/FCC Parts15; CANADA: CSA C22.2/IC BETS-7 | | |
| VESA Compatible | — | — | — | — | — | | |
| Carton Dimensions (W x H x D) | 67.5" x 40.0" x 13.1" | 63.6" x 37.2" x 11.2" | 59.7" x 34.0" x 11.2" | 53.0" x 31.4" x 10.0" | 45.7" x 27.5" x 10.0" | | |
| Gross Weight (with stand) | 105.9 lbs. | 92.6 lbs. | 81.6 lbs. | 66.2 lbs. | 50.7 lbs. | | |
| Warranty | Y (1 year) | Y (1 year) | Y (1 year) | Y (1 year) | Y (1 year) | | |

*HID (Human Interface Device Profile) compliant keyboards are available. AZDP (Advanced Audio Distribution Profile) compliant audio devices are available.