

LME-40X8

1. 40" 16:9 WXGA LCD Display
2. 16.77 Million Colors
3. High Contrast Ratio (800:1)
4. High Brightness (500 cd/m²)
5. Pixel Resolutions 1366 x 768 Pixels
6. Multi-scanning PC Monitor Support Up to 1280 x 1024
7. 170 Degrees Viewing Angle
8. RS-232 Control Port / RJ-45 Control Port
9. Built-In Speaker: 10W + 10W
10. NTSC/PAL/PAL-M/PAL-N Video System Supported



Specification	LME-40X8
Display	
Screen Size	885.168 mm x 497.664 mm (40" Diagonal)
Aspect Ratio	16 : 9
Number of Pixels	1366 (H) x 768 (V)
Pixel Pitch	0.648 mm (H) x 0.648 mm (V)
Contrast Ratio	800 : 1
Brightness	500 cd/m ²
Displayable Colors	16.77 Million Colors
Viewing Angle	170°
Response Time	16 msec
Signals	
Synchronization (Auto Detect)	
Horizontal Frequency	15KHz / 31~69 KHz
Vertical Frequency	50~85 Hz
Video System	480i, 480p, 720p, 1080i SDTV/EDTV/HDTV, NTSC/PAL/PAL-M/PAL-N
RGB Resolution	Up to 1280 x 1024 (SXGA)
RGB/DVI	
DVI Input (with HDCP)	DVI-D 24 pin x 1
RGB Input	D-Sub 15-pin x 1
RGB Output	D-Sub 15-pin x 1
Audio Input	RCA-pin (L/R) x 2 Sets
Audio	
Inner Speaker Output	10W x 2
Video Capability	
NTSC Tuner Input	RF 181CH x 1
Composite with S-Video	RCA-pin x 2 for Composite Video Mini DIN 4-pin x 2 for S-Video S-Video owns the priority
Component Video Input	RCA-pin x 2 Sets (Y/CB/CR, Y/PB/PR auto detect)
Audio Input	RCA-pin (L/R) x 4 Sets
Audio Output	RCA-pin (L/R) x 1 Set
External Subwoofer Output	RCA-pin Type x 1
Control Port	
RS-232	D-Sub 9-pin x 1
RJ-45	RJ-45 x 1
General	
Power Supply	100V~240V/50~60Hz
Power Consumption	
Dimension W/Stand (WxHxD)	1198mm x 649mm x 221.5mm / 47.17" x 25.55" x 8.72"
W/O/Stand (WxHxD)	1198mm x 600mm x 115mm / 47.17" x 23.62" x 4.52"
Weight W/Stand	25 kg
W/O/Stand	24 kg

Design and specifications are subject to change without notice.