



- 1280 x 768 native resolution
- 170° horizontal/vertical viewing angle
- 500:1 contrast ratio
- 450 cd/m² brightness (typical)
- Ultra-narrow 3.9" profile
- Digital/analog interface
- S-Video, Composite, VGA, DVI and Component inputs
- Picture-in-Picture and Picture-by-Picture

The Samsung SyncMaster 3231 is a flexible high-end 32" LCD display that's just 3.9" deep. Its ultra-wide 170° horizontal and vertical viewing angles make it visible from almost any angle, so it's perfect for videoconferences, commercial signage applications and more. Picture-in-Picture and Picture-by-Picture allow simultaneous PC/Video viewing. And with a 1280 x 768 resolution, 500:1 contrast ratio, 450 cd/mi brightness level and more, every image you display is sharper, more colorful, more impactful.

323T

32" Digital/Analog LCD Display





323T



32" Digital/Analog LCD Display

Specifications	
Panel	a-si TFT/PVA
Viewable Size	32"
Native Resolution (Optimum)	1280 x 768
Maximum Addressable Resolution	1600 x 1200 (UXGA) Analog Only
Pixel Pitch	0.537 mm
Brightness (Typical)	450 cd/m ²
Contrast Ratio	500:1
Colors Supported	16.7M
Viewing Angle (H/V)	170°/170°
Interface	Analog/Digital
Input Video Signal	Analog RGB, DVI Digital Link, S-Video, Component/HDTV
Sync Type	Separate H/V, Composite H/V, SOG
Input Connectors	15-Pin D-Sub, DVI-D, S-Video, BNC Connector, Component, HDTV, External Control, Audio
Horizontal Frequency, Analog	30 – 70 kHz
Horizontal Frequency, Digital	30 – 50 kHz
Vertical Frequency	55 – 85 Hz (60 Hz @ WXGA)
Bandwidth	90 MHz
Plug and Play	DDC 1/2B
Power Consumption	150 Watts Max
Emission Standard	TCO '95
Mac Compatibility	Yes
Sun Compatibility	Yes
Optional Accessories	10-Watt Multimedia Speakers, Wall Mount, Table Stand
Available Colors	Black
Dimensions (W x H x D)	With Stand: 30.9" x 21.7" x 8.8", Without Stand: 30.9" x 19.6" x 3.9"
Net Weight	40.1 Lbs.
Parts/Labor/Backlight Warranty	3/3/3 Years



Product Information 1-866-542-7214

Product Support 1-800-SAMSUNG www.samsungusa.com/monitor

© 2004 Samsung Electronics America, Inc. Specifications and design are subject to change without notice. Non-metric weights and measurements are approximate. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective manufacturers and companies.

