

Delta 32" LCD TV

New Faroudja DCDi and True Video Enhancement Technology

The newly developed Faroudja DCDi provides excellent performance of de-interlacing and stable images without jaggy edges and flip-flops while viewing from conventional analog sources.

High performance digital decoder converts analog signals to digital ones, and suppresses any image distortions. The Cross-Color-Suppress Technology & True Video Enhancement Technology provides you with enhanced and dynamic color reproduction.

High Brightness, Contrast Ratio and Wide Viewing Angle

Wide viewing angle technology allows watching the TV from a diverse direction. With Advanced Color Calibration Technology provides fine tuning function for better color tone. Through Gamma Calibration technology, it provides you with images at vibrant brightness and smooth gradation.

Easy and Rich AV I/O connections

Easy and rich AV input and output connection design provides an ergonomic way to hook up any Video, Audio devices from both sides of the rear cover. Abundant I/O ports allow a variety of video and audio hookup.

Slim & Stylish Design

A slim and stylish design coupled with small footprint further enhances the ergonomics and practical use of the TV.

Environment Friendly Design

EPA Energy Star compliant and low operation power consumption and with a stand-by power consumption at less than 2W makes this product an environment friendly product.



Delta's 32" LCD TV is designed with state-of-the-art DCDi, Faroudja True Color video enhancement technologies, rich and easy AV I/O connection and dynamical sound quality. They bring the highest quality of audio, visual and multimedia enjoyments to you.



Delta 32" LCD TV Specifications

Panel Size	32" Color TFT Active Matrix LCD.	
Resolution	1366x768	
Aspect Ratio	16:9	
Response Time	16.7ms (gray to gray)	
Contrast Ratio	800:1	
Maximum Brightness	550 nits	
Viewing Angle	Horizontal: 170°, Vertical: 170°	
Display Colors	16.7 million True Color (24-bit)	
Color Saturation	NTSC 75%	
PC Compatible Frequency (DVI or D-Sub)	VESA Standard Timing: 1366x768, 1280x720, 1280x1024, 1024x768, 800x600, 640x480, 720x400 H sync: 30 ~ 80 KHz, V sync: 50 ~ 75 Hz	
HDTV Compatibility	480i, 480P, 720P, 1080i	
Video Compatibility	NTSC, PAL/SECAM (Option)	
TV Compatibility	NTSC, PAL/SECAM (Option)	
Video Features	Aspect Ratio Conversion (4:3/16:9) PIP/POP (Video and Graphic, Video and Video) DCDi, (Directional Correlational De-Interlacing) CCS (Cross Color Suppressor) Auto Cinema mode 3:2/2:2 Pull Down 3D Noise Reduction Farouja True Life Video Enhancement	
Audio Features	Build in Speakers, 9W x 2ch Volume/Bass/Treble/Balance Controls BBE (Option) SRS (Option) Stereo/MTS/SAP	
Other Features	Close Caption/V-Chip	
Terminals	Front	Input1: 1 CVBS, 1 LR Output1: 1 Stereo mini-jack for Headphones
	Rear	Input2: 1 DVI-HDCP, 1 LR Input3: 1 VGA, 1 LR (mini-jack) Input4: 1 Component Video (YPbPr, HDTV ready), 1 LR Input5: 1 Component Video (YPbPr, HDTV ready), 1 LR Input6: 1 S-Video, 1 CVBS, 1 LR Tuner: 1 Tuner for NTSC Output: 1 Audio output, 1 LR Factory port: VGA
Remote Control Unit	Infrared remote controller	
Wall/Arm Mount	VESA® FPMPMI™ compliant 8-hole 100x100mm and 75x75mm	
Dimension (W x H x D)	Unit: 798 x 641 x 235 mm (with base)	
Weight	Net: 18 Kg Gross: 22 Kg	
AC Power Input Range	100~220V _{AC} , 60/50Hz	
Power Consumption	Normal < 180W, Off < 2 W	
Power Management	EPA Energy Star® compliant	
Lamp Life Time (min)	50,000 hours	

All Features, specifications, model numbers are subject to change without notice.

All Trademarks belong to their registered owners.



TAIWAN
DELTA ELECTRONICS, INC.
 Display Business/Chungli Plant
 3, Tung Yuan Road, Chungli Industrial Zone,
 Taoyuan Shien 320, Taiwan,
 Republic of China
 TEL:+886-3-4526107
 FAX:+886-3-462-1442
 Email:P.J.sales@delta.com.tw

JAPAN
DELTA ELECTRONICS (JAPAN) INC.
 Delta Shibadaimon Building
 2-1-14 Shibadaimon,
 Minato-Ku, Tokyo, 105-0012,
 Japan
 TEL:+81-3-5733-1177 / 1111
 FAX:+81-3-5733-1277
 Email: 4th_SG@dej.co.jp

U.S.A
DELTA ELECTRONICS CORPORATION
 4405 Cushing Parkway
 Fremont, CA 94538
 U.S. A.
 TEL:+1-510-668-5100
 FAX:+1-510-668-0680
 Email:dting@delta-corp.com

EUROPE
DELTA ELECTRONICS EUROPE
 Wegalaan 16
 2132 JC Hoofddorp
 The Netherlands
 TEL:+31-23-566-8928
 FAX:+31-23-566-8910
 Email:thott@euro.delta-corp.com

THAILAND
DELTA ELECTRONICS(THAILAND) INC.
 714 Soi e5, Epe, Bangpoo Industrial
 Estate km37, Sukhumvit Rd.,
 Samutprakarn 10280,
 Thailand
 TEL:+662-709-3200
 FAX:+662-709-3206