



LME-32X81

1. 32" 16:9 WXGA LCD Display
2. 16.77 Million Colors
3. High Contrast Ratio (800:1)
4. High Brightness (550 cd/m²)
5. Native Resolutions 1366 x 768 Pixels
6. Multi-scanning PC Monitor Support Up to 1280 x 1024
7. 170 Degrees Viewing Angle
8. RS-232 Control Port
9. DVI with HDCP



Optional Detachable Speakers, 10W + 10W, sold separately.

(Shown with optional side speakers)

Specification	LME-32X81
Display	
Screen Size	697.68 mm x 392.26 mm (32" Diagonal)
Aspect Ratio	16 : 9
Native Resolution	1366 (H) x 768 (V)
Contrast Ratio	800 : 1
Brightness	550 cd/m ²
Displayable Colors	16.77 Million Colors
Viewing Angle	170°
Response Time*	12 msec
Signals	
Synchronization (Auto Detect)	
Horizontal Frequency	15KHz / 31~69 KHz
Vertical Frequency	60 Hz
Video System	480i, 480p, 720p, 1080i SDTV/EDTV/HDTV, NTSC
RGB Resolution	Up to 1280 x 1024 (SXGA)
RGB/DVI	
DVI Input (with HDCP)	DVI-D 24 pin x 1
RGB Input	D-Sub 15-pin x 1
RGB Output	D-Sub 15-pin x 1
Audio Input	RCA-pin (L/R) x 2 Sets
Audio	
Detachable Side Speakers	10W x 2 (Sold Separately)
Video Capability	
NTSC Tuner Input	RF 181CH x 1
Composite with S-Video	RCA-pin x 2 for Composite Video Mini DIN 4-pin x 2 for S-Video S-Video owns the priority
Component Video Input	RCA-pin x 2 Sets (Y/CB/CR, Y/PB/PR auto detect)
Audio Input	RCA-pin (L/R) x 4 Sets
Audio Output	RCA-pin (L/R) x 1 Set
External Subwoofer Output	RCA-pin Type x 1
Control Port	
RS-232	D-Sub 9-pin x 1
General	
Power Supply	100V~240V/50~60Hz
Power Consumption	190W +/- 10%
Dimension (W/O Speaker) W/Stand	805.9 mm x 561.0 mm x 218.8 mm / 31.73" x 22.08" x 8.60"
W/OStand	805.9 mm x 507.9 mm x 109.5 mm / 31.73" x 20.00" x 4.30"
Weight (W/O Speaker) W/ Stand	16 kg / 35.27 lbs
Optional Accessory	
Wall Mount Bracket	Horizontal Mount with 4 Selectable Inclination Angles

Design and specifications are subject to change without notice.

*Response times quoted are gray-to-gray.