

# 400PX

# 400PXn

## 40" Analog/Digital Network LCD Display



- MagicNet™ X Ethernet LAN connectivity (400PXn)
- 450 cd/m<sup>2</sup> brightness
- 1366 x 768 native resolution
- 1200:1 contrast ratio
- Fast 8 ms response time
- 178° horizontal/vertical viewing angles
- Anti-image retention technologies

imagine communicating clearly without saying a word. The Samsung 400PX and 400PXn 40" LCD monitors deliver your information and your messages in big, bold, bright fashion. In lobbies or in lunchrooms, these leading-edge monitors feature 1200:1 contrast ratios, 450 nits brightness, 178° viewing angles and fast 8 ms response times. And the 400PXn can be networked through an existing LAN, allowing you to send content from a single source to many monitors and eliminating the need for any remote PCs. With the Samsung 400PX and 400PXn, it's not hard to imagine.



# 400PX 400PXn



## 40" Analog/Digital Network LCD Display

### Features

#### DNie™

Samsung's proprietary DNie™ technology provides optimized motion display, natural color, increased contrast, increased brightness and stunning detail.

#### MagicNet™ X

The server can send files to the clients after registering to the schedule. Or the client can search for files registered in the server library, select files to be received, and play them after receiving them via the network.

#### Multi Display Control (MDC)

Control up to 10 units from your PC. Just open supplied MDC software, list the units to be controlled, and click on the functions to display.

#### Video Wall

Built-in Image Enlarging Processor supports 2 x 2, 3 x 3, 4 x 4, 5 x 1 and 1 x 5 video walls. You don't need any Video Controller Device. And to use Video and PC Interface, an additional Input Signal Distributor is not necessary.


#### 2-Way Video Wall Display

Full mode displays the picture regardless of cabinet bezel. Natural mode considers bezel's depth and adjusts for a properly proportioned picture.

#### Vertical Image Capability

90° rotation allows vertical images or text.

### Dimensions



Specifications	400PX/400PXn
Viewable Size	40"
Panel Type	a-si TFT/PVA
Aspect Ratio	16:9
Pixel Pitch (H x V)	0.648 x 0.648 mm
Brightness (typical)	450 cd/m <sup>2</sup>
Contrast Ratio (typical)	1200:1
Viewing Angle (H/V)	178°/178°
Response Time (G to G)	8 ms
Scanning Frequency	Horizontal: 30-70 kHz, Vertical: 50-85 Hz
Maximum Resolution (H x V)	1366 x 768
Bandwidth	100 MHz
Colors Supported	16.7M
Sync Type	Separate H/V, Composite, SOG
Input Video Signal	Analog RGB (15-pin D-sub)
	DVI-D
	S-Video
	BNC Component Video/PC
	RS-232C 9-pin D-sub
	USB
	Audio (2 x RCA L/R, 1 x Stereo PC)
	Video Composite
Input Connectors	Analog RGB (15-pin D-sub)
	S-Video
	BNC Component Video/PC
	RS-232C 9-pin D-sub
	Speaker (10W x 2)
	Video Composite
Power Consumption	230 watts
Color	Black/Black
Included Accessories	MDC software
	User manual
	RCA adapter (4 pcs)
	Power cable
	Remote controller
	Table-top stand
Optional Accessories	Speaker: SP-L400PB/S (10 watts x 2), Wall Mount Bracket: WMB-4050PS (VESA compatible)
Dimensions (W x H x D)	38.2" x 24.8" x 8.8" (without stand: 38.2" x 22.9" x 4.7")
Net Weight	51.8 lbs.
Plug and Play	DDC 2B
Compatibility	Windows, Mac, Sun
Special Features	Anti-image retention function (DNie), PIP/PDP/POP, HDCP (HD copy protection), Safety lock, Video wall (2 x 2, 3 x 3, 1 x 5, 5 x 1, 4 x 4)
Magic Technologies	XP-based MagicNet™ (400PXn)
Safety/Regulation	FCC Class A, UL, CSA, TUV, NEMCO, CE, NUTEK

Product Information: 1-866-542-7214 [www.samsung.com/monitor](http://www.samsung.com/monitor)

Product Support: 1-800-SAMSUNG



©2007 Samsung Electronics America, Inc. Samsung is a registered mark of Samsung Electronics Corp., Ltd. Specifications and design are subject to change without notice. See [www.samsung.com](http://www.samsung.com) for detailed information. Printed in USA. 400PXn10/07R2