



FEATURES

Ready to use plasma TV: speakers, tuner, amplifier

Multi - connections: Video, S-Video, Scart, YuV, computer connection (RGB input), DVI in

Integrated tuner with various features : PIP, PAT, text, ...

Brightness 1000 cd/m²
Contrast ratio : 1000 : 1

Fan free

Stand included. Wallmount optional

BENEFITS

Directly plug your TV antenna on your plasma and enjoy your favorite programs

Plug and play directly your appliances on plasma, DVD on S-Video or YuV, VCR on Scart, PC

Choose your format (4/3, 16/9, cinerama, ...)

Highest brightness performances to enjoy vivid colors in all conditions.

New "cold" panel technology reduces heat on plasma. Fan is no use at all.

Ease of use solution and propose alternatives

THOMSON SCENIUM

42 WM 03 ST

Technical data :

BRAND	
Brand	SCENIUM
COLOR	
Color	Silver
SERVICE	
TAK Interactive TV	-
PICTURE	
Screen size WxH (mm) / diagonal (cm)	932 x 532 / 106
Screen size WxH / diagonal (inches)	36.7 x 20.9 / 42
Aspect ratio	16/9
Computer signal compatibility	VGA, SVGA, XGA, SXGA, MAC
Resolution (H x V)	852 x 480
Number of Pixels	852 x 480 x 3
Pixel Size in mm	1.08 x 1.08
Displayable colors Levels / million	16.77
Contrast ratio	1000 : 1
Luminosity in cd/m ²	1000
Viewing angle (Horizontal & Vertical)	160°
Video standard (1)	PAL, SECAM, NTSC 3.58 & 4.43
Video standard (2)	PAL 60 Hz 525 lines
Filter	-
Digital Zoom	-
Frequency	50/60 Hz progressive
Format control	PC-mode 4:3 centre, 16:9
Teletext / Nb of pages / Level	Yes 1020 / 2.5
P I P	Yes
P A P	-
P A T	Yes
TV Guide	-
Burn in reduction	-
SOUND	
Sound Type	Stereo
Music Power (Watt)	2 x 10
Attached external speaker	-
CONNECTORS	
RGB - input 1 (Analog)	Yes
RGB - input 2 (Analog)	-
RGB - input 3 (Digital)	-
Video input	Yes
DVI	Yes
S-Video	Yes
DVD/HD	Scart
External control	RS232
Audio	Yes
Audio output	Yes
GENERAL DATA	
Monitor dimensions (WxHxD in mm)	1040x 648 x 95
Packaging Size Monitor (WxHxD in mm)	1230 x 960 x 470
Packaging Size Other (WxHxD)	-
Monitor Weight Net (in kg)	31.2
EAN Code	3244480130674
Instruction Booklets	F/GB/D/I/E
Instruction Booklets	-
OSD display languages	F/GB/D/I/E
Power supply	220-240 V 50/60Hz
Consumption (in W)	380
Standby consumption (in W)	5
Intensity (in A)	3.3
Operating temperature (min / max in C°)	0 / 40
Operating Humidity (min / max in %)	20 / 80
ATTACHMENTS	
Remote Control Type "Navilight"	VCR/DVD/HIFI/SAT compatible
Remote Control Reference	RCT4157S
Package content (1) - Tuner Box	-
Package content (2) - D-VHS	-
Package content (3) - DVD	-
Package content (4) - Dolby Digital Ampl	-
Package content (5) - 5 External speaker	-
Package content (6) - 4 Speakers stands	-
Optional Desktop stand	-
Desktop stand	Yes (Provided with Plasma)
Wall-mounting Bracket / optional	ACC913 / Yes
Stand / optional	-
Cable Scart-Cinch V75-5	-
Cable VGA	-

Cable DVI	Yes
Cable RS232C	-
Cables S-VHS (3m)	-
Cable S-VHS (1,5 m)	-
Cable Cinch (1,5 m)	-
Cable Loudspeakers (20 m)	-
Cables Scart	-
Cable Cinch Video/Audio	-
Aerial cable	-
Ferrite cores	-

CONNECTORS WITH TUNER BOX

Scart 1	-
Scart 2	-
Scart 3	-
Cinch audio in / out	-
PC in front	-
PC out Rear	-
DVI out	-
RS232	-