

## BeoVision 8



DESIGNER	David Lewis
DIMENSIONS (WxHxD) / WEIGHT	86 x 52 x 24 cm + stand / approx. 21 kg (32")
POWER CONSUMPTION	Typical 150 W, standby < 1 W (32")
HD-READY	Yes - 720p, 1080i, 50/60 Hz
TELETEXT	Yes – level 1.5, 2000 memory pages
TV SYSTEM	Connect external ATSC or set-top box
LCD	16:9 TFT LCD (High glare and Low-reflection Coating)
RESOLUTION	1366 x 768, HD-Ready
LUMINANCE OF WHITE	typ. 500 cd/m <sup>2</sup> (center of screen)
CONTRAST RATIO	typ. 1200:1 (center of screen)
RESPONSE TIME	typ. 6 msec
VIEWING ANGLE	typ. +/-88 degrees both vertical and horizontal
MENU LANGUAGES	English, Danish, Dutch, Spanish, Italian, German, French, Swedish
IR CONTROL OUTPUT	Built in – Supports two STB (IR-blaster included)
LOUDSPEAKERS	Stereo Channel with center bass
CABINET PRINCIPLE	Closed box (midrange/tweeter) / Bass Reflex (center bass)
LOUDSPEAKER DRIVERS	Midrange/tweeter: 50 mm full range Bass: 100 mm bass / midrange
AV-CONNECTORS	2 x 21-pin SCART sockets, 3 x phono sockets (Y-Pb-Pr), 3 x phono sockets (CVBS/L-R), 1 x VGA socket, 1 x HDMI socket
CAMCORDER / AUX	3 x Phono sockets (video in/audio L-R in), auto detection (video)
OPTIONAL EXTRA	System module (Master Link, 1 x SCART socket) SCART to XXX adaptor