

N4060w

40" NEXTVISION® WIDESCREEN LCD TV

WITH DNX™ IMAGE PROCESSING

Ultimate HDTV entertainment.

ViewSonic's 40" widescreen N4060w LCD TV is the perfect display to finish your high-performance home theater. Prepare to be amazed by PERFECTLY SHARP, CRYSTAL CLEAR OFF-THE-AIR HDTV broadcasts, DVDs, movies, games and more on the N4060w. It's packed with performance features such as DNX™ IMAGE PROCESSING TECHNOLOGY, super-fast 8ms video response time and HDMI digital video with HDCP for long-term compatibility. View HD movies and television in their native format thanks to the widescreen aspect ratio. Experience SRS TRUSURROUND XT DIGITAL AUDIO for a theater-like sensation. The N4060w includes a universal remote control so that you can get rid of the clutter and control all your electronic entertainment from a single remote. This elegantly-crafted, slim panel LCD TV adds a touch of style to any décor.



Single control
universal remote for all
entertainment peripherals.

INSPIRE ENVY

> Experience widescreen HDTV

Enjoy a widescreen theater experience and high-definition picture quality with this display's widescreen aspect ratio, true HDTV capability, and wide viewing angles.

> DNX™ image processing technology

DNX image processing provides superior picture quality through precision deinterlacing, 10-bit color processing, advanced scaling and Pixelboost for smoother, sharper full-motion video with incredibly rich colors.

> Vivid graphics, clear text, stunning TV

Ultra-high brightness of 500 nits (typ), high contrast ratio of 1000:1 (typ), and 1360x768 optimum PC resolution provides vibrant video and crisp data images on the desktop or in the living room.

> Expand your options with plug-and-play connectivity and universal remote control

This true HDTV provides the ultimate viewing experience with plug-and-play, high-end connectivity for set-top boxes, DVDs, game consoles and camcorders.

> OptiSync® technology featuring HDMI

Add versatility to your LCD TV with support for HDMI with high-definition content protection (HDCP) and analog (VGA) signals, plus component, S-video, composite, and TV/cable input.

> Powerful high-fidelity audio

It's all accompanied by an ultra-high fidelity 20-watt SRS TruSurround XT audio system that completes the entertainment experience.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES



ViewSonic 

the choice of professionals

N4060w

40" NEXTVISION® WIDESCREEN LCD TV WITH DNX™ IMAGE PROCESSING



LCD	Type	40" (39.9" viewable) color TFT active matrix, wide LCD
	Display Area	34.8" horizontal x 19.6" vertical; 40" diagonal
	Native Resolution	1366x768
	Contrast Ratio	1000:1 (typ)
	Viewing Angles	170° horizontal, 170° vertical
	Response Time	8ms
	Light Source	Long life, 60,000 hrs. (typ)
	Brightness	500 cd/m2 (typ)
	Aspect Ratio	16:9
	Glass Surface	Haze 44%, hard coating (3H)
INPUT	PC	RGB analog (75 ohms, 0.7 Vp-p)
	TV	TV/cable, composite (RCA), component YPbPr/YCbCr, S-video
	Audio	3.5mm mini stereo audio in/out and RCA (left/right) audio in
	RGB Frequency	F _H : 30~64kHz, F _V : 60~75Hz
	Sync	H/V separated (TTL)
	Digital	HDMI (with HDCP and audio support)
	Tuner	NTSC/ATSC
AUDIO OUTPUT	Speakers	2x10-watt SRS TruSurround XT
COMPATIBILITY	PC	1360x768 (preferred), 1024x768, 1280x720
	Mac®*	Power Mac™ G3/G4/G5 up to 1280x1024, 1280x720 (preferred)
INPUT SIGNAL	TV/Video Comp.	480i, 480p, 720p, 1080i
CONNECTOR	Analog	15-pin mini D-sub (VGA)
	Digital	HDMI
	Power	3-pin plug
POWER	Voltage	AC 90~240V (universal), 60/50Hz
	Consumption	260W (typ)
CONTROLS	Basic	Power, enter, channel +/-, volume +/-, menu
	OnView® (PC Mode)	Auto adjust, contrast, brightness, H. position, V. position, H. size, fine tune, aspect ratio, information, text/graphic mode, color temperature
	(Video Mode)	Picture (contrast, brightness, color, tint, sharpness, aspect ratio, color temperature), sound (volume, balance, bass, treble, input menu (TV, AV, S-video, YCbCr, YPbPr, HDMI, VGA), parental control (caption, change password, TV ratings, MPAA movie ratings, V-chip temporary disable), PIP (input, POP, mode disable, audio, SWAP, size/position), set up (OSD H/V position), time out, transparency, OSD color, language, memory recall
	(TV Mode)	MTS, TV/CATV, auto scan, set channel, channel delete, label, favorite, fine tune
OPERATING CONDITIONS	Temperature	32~104°F (0~40°C)
	Humidity	20~85% (non-condensing)
DIMENSIONS (W x H x D)	Physical (mm)	808mm x 628mm x 243mm (with stand)
	Physical (in.)	40.0" x 29.7" x 11.0" (with stand)
WEIGHT	Net	72.6 lb. (33.0 kg) (with stand)
	Gross	88.0 lb. (40.0 kg) (with stand)
REGULATIONS		cUL, NOM, CB, FCC-B
PACKAGE CONTENTS		LCD TV display, power cable, remote control with batteries, RCA A/V cable, Quick Start Guide, User Guide
WARRANTY		One-year limited warranty on parts and backlight



ISO 9001:2000
FM 40187



ISO 14001:1996
FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. DNX is a registered trademark of Pixelworks, Inc. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2006 ViewSonic Corporation. All rights reserved. [12694-00B-11/05] N4060w-1

ViewSonic 

the choice of professionals

For more product information, visit us on the web at ViewSonic.com