N4785p

47" WIDESCREEN 1080P LCD HDTV

WITH THREE HDMI INPUTS

Brilliant 1080p entertainment.

ViewSonic's incredible N4785p 47" LCD HDTV transports you to new heights in home entertainment. Feel the colors and details in movies and games made possible only by full 1080p high-definition performance. 1920x1080p resolution delivers 100% of your HD signal for unsurpassed image precision. High contrast ratio and brightness provide richer colors, while ClearPicture™ technology ensures extreme clarity in fast action movies and sports. Dolby® Digital stereo sound optimizes your viewing experience. Three HDMI inputs let you add Blu-Ray, HD-DVD, cable or satellite and other digital components for complete, uncompromised HD entertainment at home.



STEP UP TO A HIGHER LEVEL OF PERFORMANCE

> Experience widescreen HDTV

Enjoy a widescreen theater experience and high-definition picture quality with this display's widescreen aspect ratio, full HD (FHD) 1080p HDTV capability, and wide viewing angles.

> ClearPicture™ image processing delivers clearer, crisper, sharper images

ClearPicture™ image processing eliminates noise, increases contrast and detail and optimizes color for rich, vibrant images. High-definition images look amazing and even standard television images are unbelievably smooth and sharp.

> Vivid graphics, clear text, stunning TV

Ultra-high brightness of 500 nits (typ), high contrast ratio of 1500:1 (typ), and 1920x1080 optimum resolution provide vibrant video and lifelike images.

> OptiSync® technology now features three HDMI

Add versatility to your LCD TV with support for HDMI with high-definition content protection (HDCP) and analog (VGA) signals, plus 2 component, S-video, 2 composite, and 2 TV/cable inputs.

> Powerful high-fidelity audio

It's all accompanied by high fidelity

Dolby® Digital stereo sound that completes
the entertainment experience.











N4785p

47" WIDESCREEN 1080P LCD HDTV WITH THREE HDMI INPUTS





LCD	Туре	47" color TFT active matrix, wide LCD
	Display Area	40.9" horizontal x 23.0" vertical; 47" diagonal
	Native Resolution	1920x1080
	Contrast Ratio	1500:1 (typ)
	Viewing Angles	176° horizontal, 176° vertical
	Response Time	6.5ms
	Light Source	Long life, 50,000 hrs. (typ)
	Brightness	500 cd/m2 (typ)
	Aspect Ratio	16:9
	Glass Surface	Anti-glare, anti-reflective coat
INPUT	PC	RGB analog (75 ohms, 0.7 Vp-p)
	TV	S-video, TV/cable x2, composite (RCA) x4,
		component YPbPr/YCbCr x2
	Audio	3.5mm mini stereo audio in/out and RCA x2 (left/right) audio in
	RGB Frequency	F _h : 30~64kHz, F _v : 60~75Hz
	Sync	H/V separated (TTL)
	Digital	HDMI x3 (with HDCP and audio support)
	Tuner	ATSC/NTSC/QAM
	RS-232c	Control port
AUDIO OUTPUT	Speakers	2x15-watt
AUDIO OUTFUT	RCA	
COMPATIBILITY	PC PC	Left/right 640x480, 800x600, 1024x768, 1280x720, 1280x768,
	rC	1280x1024, 1360x768, 1440x900, 1680x1050
INDUT CICNIAL	TV/A/:dea Carer	
INPUT SIGNAL	TV/Video Comp.	480i, 480p, 720p, 1080i, 1080p
CONNECTOR	Analog	15-pin mini D-sub (VGA)
	Digital	HDMI x3
	Power	3-pin plug
CONTROLS	Voltage	AC 10–240V (universal), 50–60Hz
	Consumption	242W (typ)
	Basic	Power, enter, channel +/-, volume +/-, menu
	Picture	Picture mode, brightness, contrast, color, tint,
		sharpness, color temperature
	TV/Audio	Balance, bass, treble, surround, reverb, equilizer, SPDIF type,
		auto volume control, tuner mode, auto scan, channel skip,
		MTS, audio language
	Set Up	OSD language, aspect ratio, blue mute, time setup,
		aloned contion mamory recall shapped block program block
		input block, change password, clear all
OPERATING	Temperature	input block, change password, clear all 32–104°F (0–40°C)
CONDITIONS	Humidity	input block, change password, clear all 32–104°F (0–40°C) 10–65% (non-condensing)
CONDITIONS		input block, change password, clear all 32–104°F (0–40°C) 10–65% (non-condensing) 44.8"x 32.6"x 11.6" (1137mm x 828mm x 294mm)
CONDITIONS DIMENSIONS (W x H x D)	Humidity Physical with stand Physical without stand	input block, change password, clear all 32–104°F (0–40°C) 10–65% (non-condensing) 44.8"x 32.6"x 11.6" (1137mm x 828mm x 294mm) 44.8"x 30.4"x 4.9" (1137mm x 772mm x 124mm)
CONDITIONS DIMENSIONS (W x H x D)	Humidity Physical with stand Physical without stand Net with stand	32–104°F (0–40°C) 10–65% (non-condensing) 44.8"x 32.6"x 11.6" (1137mm x 828mm x 294mm) 44.8"x 30.4"x 4.9" (1137mm x 772mm x 124mm) 75.8 lb. (34.4 kg)
CONDITIONS DIMENSIONS (W x H x D)	Physical with stand Physical without stand Net with stand Net without stand	input block, change password, clear all 32–104°F (0–40°C) 10–65% (non-condensing) 44.8"x 32.6"x 11.6" (1137mm x 828mm x 294mm) 44.8"x 30.4"x 4.9" (1137mm x 772mm x 124mm) 75.8 lb. (34.4 kg) 67.0 lb. (30.4 kg)
CONDITIONS DIMENSIONS (W x H x D) WEIGHT	Humidity Physical with stand Physical without stand Net with stand	input block, change password, clear all 32–104°F (0–40°C) 10–65% (non-condensing) 44.8"x 32.6"x 11.6" (1137mm x 828mm x 294mm) 44.8"x 30.4"x 4.9" (1137mm x 772mm x 124mm) 75.8 lb. (34.4 kg) 67.0 lb. (30.4 kg) 89.1 lb. (40.4 kg)
CONDITIONS DIMENSIONS (W x H x D) WEIGHT	Humidity Physical with stand Physical without stand Net with stand Net without stand Gross with stand	input block, change password, clear all 32–104°F (0–40°C) 10–65% (non-condensing) 44.8"x 32.6"x 11.6" (1137mm x 828mm x 294mm) 44.8"x 30.4"x 4.9" (1137mm x 772mm x 124mm) 75.8 lb. (34.4 kg) 67.0 lb. (30.4 kg) 89.1 lb. (40.4 kg) 200mm x 400mm; 200mm x 600mm
OPERATING CONDITIONS DIMENSIONS (W x H x D) WEIGHT VESA® MOUNT RECYCLE/DISPOS	Humidity Physical with stand Physical without stand Net with stand Net without stand Gross with stand	input block, change password, clear all 32–104°F (0–40°C) 10–65% (non-condensing) 44.8"x 32.6"x 11.6" (1137mm x 828mm x 294mm) 44.8"x 30.4"x 4.9" (1137mm x 772mm x 124mm) 75.8 lb. (34.4 kg) 67.0 lb. (30.4 kg) 89.1 lb. (40.4 kg) 200mm x 400mm; 200mm x 600mm The lamp in this product contains mercury. Please dispose of
CONDITIONS DIMENSIONS (W x H x D) WEIGHT	Humidity Physical with stand Physical without stand Net with stand Net without stand Gross with stand	input block, change password, clear all 32–104°F (0–40°C) 10–65% (non-condensing) 44.8"x 32.6"x 11.6" (1137mm x 828mm x 294mm) 44.8"x 30.4"x 4.9" (1137mm x 772mm x 124mm) 75.8 lb. (34.4 kg) 67.0 lb. (30.4 kg) 89.1 lb. (40.4 kg) 200mm x 400mm; 200mm x 600mm The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.
CONDITIONS DIMENSIONS (W x H x D) WEIGHT VESA® MOUNT RECYCLE/DISPOS	Humidity Physical with stand Physical without stand Net with stand Net without stand Gross with stand	input block, change password, clear all 32–104°F (0–40°C) 10–65% (non-condensing) 44.8"x 32.6"x 11.6" (1137mm x 828mm x 294mm) 44.8"x 30.4"x 4.9" (1137mm x 772mm x 124mm) 75.8 lb. (34.4 kg) 67.0 lb. (30.4 kg) 89.1 lb. (40.4 kg) 200mm x 400mm; 200mm x 600mm The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws. cUL, FCC, NOM, EN 55013, CB, Dolby®
CONDITIONS DIMENSIONS (W x H x D) WEIGHT	Humidity Physical with stand Physical without stand Net with stand Net without stand Gross with stand	input block, change password, clear all 32–104°F (0–40°C) 10–65% (non-condensing) 44.8"x 32.6"x 11.6" (1137mm x 828mm x 294mm) 44.8"x 30.4"x 4.9" (1137mm x 772mm x 124mm) 75.8 lb. (34.4 kg) 67.0 lb. (30.4 kg) 89.1 lb. (40.4 kg) 200mm x 400mm; 200mm x 600mm The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.





ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2007 ViewSonic Corporation. All rights reserved. [13762-00B-11/07] N4785p-1