

40" WXGA LCD Multimedia Display



- 800:1 Contrast Ratio
- 550 cd/m2 Brightness
- · Native 1366 x 768 Resolution
- · Video-on-Graphics Capable
- Variable Aspect Ratio Control
- Network Ready RS-232 and RJ-45 Inputs

LCTV-40X

Display

Screen Size: 40" Diagonal
Aspect Ratio: 16:9

70.0

Resolution: 1366 X 768 WXGA (NI)

Multi-scanning PC/MAC, monitor support to 1280 x 1024

Pixel Pitch: 0.648 mm (H&V)

 Contrast Ratio:
 800:1

 Brightness:
 500 cd/m≤

 Displayable Colors:
 16.7 million

 Viewing Angle
 170 degrees

 Response:
 16 ms

Connections

Computer Inputs: (1) DVI-D 24 pin

(1) HD-15 pin

Video/HDTV Inputs: Automatic signal detection for all sources

480i, 480p, 720p, 1080i support Composite with S-Video (2) Composite Video, RCA-pin

(2) S-Video-mini DIN 4-pin (S-video Owns Priority)

(2) Component Video (Y,Cb,Cr, Y/Pb/Pr)

Tuner: (1)TV Tuner (RF),181 Channel

Audio Input: (6) RCA-pin Type (L/R)

Audio Output: (1) RCA-pin Type (L/R)

Output: (1) RCA-pin Type (L/R)
(1) External Subwoofer-RCA-pin

Network Control: (1) RS232 D-sub 9-pin , (1) RJ45

Details

Video: PIP/POP, Video-on-Graphic, CC

Audio System: 10 W + 10W BTCS Stereo, Surround, MTS/SAP, 4 Spkrs

Power Supply.: A/C 100-240V/50-60Hz, DC 12V
Power Usage: 220 W Maximum, 5 W save mode

Other Functions: Video On Graphics, 3D digital comb filter, 3:2 Pull Down,

Digital Zoom, Discreet power on/off, Bass extension circuitry-subwoofer out, CC, Adaptive Motion De-Interlacing, Advanced Video Scaling Selectable Variable/Fixed Audio Out, Surround Sound Processing, Front Panel Lock, Sleeo Timer. Static IP Address conflouration.

Table Stand, remote, VGA & power cable incld. Wall mount optional

Regulatory: FCC, UL, CE, BSMI

Dimensions/Weight: 47.2" W x 23.6" H x 4.5" D (53lbs),

With Stand 47.2"W x25.6"H x8.7"W (55lbs)



Rapid Exchange Service

In addition to our standard two year parts and labor warranty, each NetTV Display (excluding PDP) comes with one year of our exclusive Rapid Exchange Service (RES). With one call, RES either repairs or replaces your out of service monitor within 48 hours to prevent lengthy service interruption. A 2nd and 3rd years coverage is available for long term, care free service.

Accessories:

