



VIZIO

P50 HDTV

FEATURING THE LATEST IN VIDEO TECHNOLOGY, THE VIZIO P50 HDTV LIGHTS UP ANY ROOM WITH VIBRANT COLORS, SHARP, FLUID IMAGES AND AN IMPRESSIVELY WIDE VIEWING ANGLE. AND WHILE THE VIZIO P50 HDTV IS VALUE PRICED, IT ALSO OFFERS AN ELEGANT FLAT PANEL DESIGN FOR A SPECTACULAR VIEWING EXPERIENCE.



www.viziotv.com



P50 HDTV

VIZIO P50 HDTV

HIGH DEFINITION FLAT PANEL PLASMA TELEVISION

FEATURES

- 50" Diagonal Plasma Flat Panel with 16:9 Aspect Ratio.
- High Definition Television (HDTV) with a native resolution of 1366 x 768.
- Integrated NTSC and ATSC tuner allows over-the-air analog and digital broadcasts with an external antenna or cable*
- High Brightness (1000 cd/m2) providing a more vivid, brilliant picture in any environment.
- 24 bit color depth supporting 231 Billion colors.
- Multiple video format support with HDMI, component video, composite video, S-Video and RF antenna inputs allows you to enjoy video from a variety of sources.
- Wide viewing angle (>170°) so that everyone can view the picture from practically anywhere in the room.
- PIP (Picture in Picture) and POP (side-by-side) for ultimate video enjoyment while watching 2 video programs at the same time.
- 60,000 hour panel life provides over 27 years of use before half brightness (based on an average of 6 hours / day use).
- DCDi by Faroudja Low Angle De-interlacing Processing for superior video quality.
- VIZIO Universal Remote Control and stand included.

* Clear QAM signal required for Digital Cable reception.



VIZIO VIP SERVICES
Extended Warranties, Installation Services
www.viziotv.com



SPECIFICATIONS

- Panel: 50" Diagonal, 16:9 Aspect Ratio
- Resolution: 1366 x 768 pixels
- Display Compatibility: HDTV (720P)
- Signal Compatibility: 480i (SDTV), 480P (EDTV), 720P (HDTV), 1080i (HDTV)
- Brightness: 1000 cd/m2 typical
- Contrast: 10,000:1 max
- Viewing Angle: >170 degrees (horizontal/vertical)
- Inputs: 1x RF (F Connector for internal ATSC/QAM/NTSC Tuner)
2x HDMI with HDCP plus Stereo Analog Audio
2x Component YPbPr plus Stereo Audio
2x Composite Video / 2x S-Video plus Stereo Audio
1x Analog RGB plus Stereo Audio
1x Service Port
- Outputs: 1 x Analog Audio out (RCA)
1 x Digital Optical Audio (from DTV ATSC tuner)
- Speakers: Built-in 2 x 15 W
- Features: PIP, POP, CC, V-Chip, 3D Comb Filter, Zoom, Freeze, DCDi De-Interlace, 3:2 or 2:2 Reverse Pull-down, ATSC, with 8VSB & QAM demodulation, with MPEG-2 decoding, NTSC Video decoding via RF (Antenna, Cable or Satellite) or Video (CVBS, S-Video or Component), Progressive Scan Video via Component YPbPr, VGA or HDMI, HDTV via HDMI or Component YPbPr, Computer 640x480, 800x600, 1024x768 via VGA or 640x480 via HDMI, SRS Sound enhancement, Color Temperature of 6500K, 5400K and 9300K, Independent Red, Green and Blue adjustment for user fine tuning of color temperature.
- Power: IEC Connector for direct power line connection.
Voltage Range: 100 ~ 240VAC at 50/60 Hz Power consumption: 400W average
- Dimensions: 48.8" w x 34.2" h x 12.2" d (1240 x 868 x 310 mm) w/stand;
48.8" x 33.5" x 3.9" (1240 x 850 x 99 mm) w/o stand
- Gross Weight: 143.7 lb (65.2 kg)
Net Weight: 121.7 lbs (55.2 kg) w/stand; 124 lbs (56.4 kg) w/o stand
- Certifications: CSA, FCC Class B



OPTIONAL ACCESSORIES

Tilt Wall Mount, Flush Wall Mount, HDMI cables, Component video cables - Call 1.888.849.4623 for details.



*Product specifications are subject to change without obligation.



WHERE
VISION
MEETS
VALUE