

The Runco VideoWall™ CW-95DHD is a 2.35:1 is a 95-inch diagonal, native 1080p HD in-wall display ideal for installations where an ultra-large screen is required, but front projection is difficult to deliver because of ambient light.



Projection Device:	1080p SuperOnyx™ DMD™
Native Resolution:	1920 x 817
DTV Compatibility:	480p, 720p, 1080i, 1080p (24, 50, 60Hz)
Picture Size (16:9 screens):	95" Diagonal
Light Output:	40 Foot-Lamberts (fL)
Contrast Ratio:	450:1 ANSI
Lamp:	180W UHP
Lamp Life:	6000 hours
Power Requirements:	100–240V AC, 50/60 Hz, 510W
Operating Environments:	40°–95° F, (5°–35° C), 0%–90% Humidity (non-condensing)
Dimensions (rear assembly):	Width: 91.8 in. (2332 mm), Depth: 31.6 in. (802.64 mm), Height: 57.1 in. (1450.3 mm)
Dimensions (screen assembly)	Width: 91.8 in. (2332 mm); Depth: 1.5 in. (38.1 mm) Height: 41.74 in. (1060 mm)
Weight:	Screen: 95.0 lbs. (43.1 kg); Rear Assembly: 165 lbs. (74.8 kg)
Regulatory Approvals:	Complies with FCC Class B, CE, C-Tick
Limited Warranty:	Unit: (2) Two years parts and labor from the date of delivery to the end user Lamp
Warranty:	1000 hours or (6) six months, which ever comes first. RuncoCare™ and Runco RedCarpet™ plans are also available.
The Runco CW-95DHD Ships with:	Remote Control, (2) AAA batteries, Power Cord (US only), Installer manual, Setup Guide

Runco DHD Controller Specifications

Aspect Ratios:	4:3, 16:9, Letterbox, VirtualWide™, Native, VirtualCinema™ and Cinema
Video Processing:	ViVix III™ 1080p output
Video Standards:	NTSC, PAL, ATSC and SECAM
Supported Signal Timings:	1080p (23.98, 24, 50, 59.94, 60), 1080i (50, 50 Australia, 59.94, 60), 720p (23.98, 24, 25, 29.97, 30, 50, 60), 576p/i, 480p/i, SCART RGB, std. PC timings
Output:	(1) HDMI v1.3 w/ HDCP and Deep Color up to 12 bits/channel; (1) RJ-11 for display control; (1) RJ-11 for display control
Inputs:	(1) Composite; (2) S-Video; (1) Component; (2) HD - R (Pr), G (Y), B (Pb), H, V; (2) HDMI v1.3 w/HDCP and Deep Color up to 12 bits/channel
Communications Control Ports:	Discrete infrared remote, (1) RS-232 9 pin connector; front panel
Screen Trigger/ Masking Output:	(3) +12 VDC, each rated at 250 mA with over-current protection
Power Requirements:	100-240V AC (auto sensing) 50/60 Hz, 40W
Dimensions:	Width: 17 1/2 in. (444.50 mm); Depth: 11 3/16 in. (284.10 mm); Height: 3 3/4 in. (95.25 mm), Weight: 13 lbs. (5.9 kg)
Included Accessories:	Runco remote, batteries, RJ-11 cable and RS-232 adapter, rack mount brackets
Features:	Highly-compatible with today's video sources, fully-compliant HDMI/HDCP repeater, full ISF™ calibration controls, easy firmware upgrades via USB or serial, customizable splash screen and side-curtain colors
BRiC Tool:	Backup, Recovery & Clone tool to saving, restoring or cloning calibrations settings