



TLT3200D Product Specification

Model TLT3200D

Model TLT3200D					
LCD Panel	Display Size	32" (16:9)	Inputs	RF (DTV)	VHF/UHF x 1 (rear)
	Response Time	8 ms		Composite	x 2 (rear)
	Pixel Size	0.017 x 0.511		S-Video	x 1 (rear)
	Resolution	1366 x 768 (WSXGA)		Component	x 2 (rear) 480i/1080i
	Color	8 bit, 16.77 M		HDMI	x 1 (rear)
	Brightness	500 cd/m2		DVI-D	X
	Contrast Ratio	800:1		PC	x 1 (rear) D-Sub
	Viewing Angle	U/D: 88/88, R/L: 88/88		RS-232C	x 1 (rear) Phone Jack Type
	Surface Treatment	Head Coating (3H)		Audio (PC)	Mic Type Jack
System	TV Signal	ATSC/NTSC	Output	Video	X
	Tuner	1 Tuner		Audio	X
	AV Signal	NTSC		Headphone	X
	Text	Closed Caption/V-Chip		S-PDIF	Optical
Video	PSM	Dynamic, Standard, Movie, Sports, PC, User		Data Service	o (Phone Jack Type)
	Picture Mode	Wide, Panorama, Zoom, 4:3, 16:9		Ext S/P	o
	Color Status Memory	o		Picture	X
	Progressive Scan	o		Picture Swap	X
Sound	Filter	3D Comb Filter		Misc	Picture Shift
	Stereo	MTS/SAP	Double Window		X
	AVL	o	Sleep Timer		10~180 min
	Sound Output (RMS)	10W x 2	On/Off Timer		o
	SSM	Flat, Music, Movie, Speech, User	Clock		o
	Surround	o	Auto Off		No signal Only
	Speaker	2 Way 4 Speaker	Auto Mute		Blue Back Only
Power	Consumption	130W	Channel Reserve		o
	Standby	> 1W	OSC		English, Spanish, French
Dimension	Set size (WxDxH, Inch)	36.73 x 9.06 x 22.05	Weight	Net (lb)	20.1
		With Stand and Speaker		Gross (lb)	Stand Detachable
		36.73 x 4.41 x 19.8			24.6
		Without Speaker			Stand Detachable