



TLT3700D

Product Specification

Model TLT3700D						
LCD Panel	Display Size	37" (16:9)	Inputs	RF (DTV)	VHF/UHF x 1 (rear)	
	Response Time	8 ms		Composite	x 1 (side), x 2 (rear)	
	Pixel Size	0.2 x 0.6		S-Video	x 1 (side), x 2 (rear)	
	Resolution	1366 x 768 (WSXGA)		Component	x 1 (rear) 480i/1080i	
	Color	8 bit, 16.77 M		HDMI	x 1 (rear)	
	Brightness	500 cd/m2		DVI-D	x 1 (rear)	
	Contrast Ratio	600:1		PC	x 1 (rear) D-Sub	
	Viewing Angle	U/D: 88/88, R/L: 88/88		RS-232C	x 1 (rear) Phone Jack Type	
	Surface Treatment	Head Coating (3H)		Audio (PC)	Mic Type Jack	
System	TV Signal	ATSC/NTSC	Output	Video	x 1 (rear)	
	Tuner	1 Tuner		Audio	x 1 (rear) L/R	
	AV Signal	NTSC		Headphone	x 1 (side)	
	Text	Closed Caption/V-Chip		S-PDIF	Optical	
Video	PSM	Dynamic, Standard, Movie, Sports, PC, User	Data Service	o (Phone Jack Type)		
	Picture Mode	Wide, Panorama, Zoom, 4:3, 16:9	Ext S/P	o		
	Color Status Memory	o	Picture	PIP, POP, PBP		
	Progressive Scan	o	Picture Swap	o		
Sound	Filter	3D Comb Filter	Misc	Picture Shift	o (PIP)	
	Stereo	MTS/SAP		Double Window	o (PBP)	
	AVL	o		Sleep Timer	10~240 min	
	Sound Output (RMS)	10W x 2		On/Off Timer	o	
	SSM	Flat, Music, Movie, Speech, User		Clock	o	
	Surround	o		Auto Off	No signal Only	
Power	Speaker	2 Way 4 Speaker	Auto Mute	Blue Back Only		
	Consumption	130W	Channel Reserve	o		
Dimension	Set size (WxDxH, Inch)	Standby	> 1W	OSC	Engl, Ital, Span, Ger, Fre	
		Weight	42.76 x 11.97 x 25.2	Net (lb)	51.8 (Display)	
			With Stand and Speaker		9.48 (Stand), 4.2 (Speaker)	
			42.76 x 4.6 x 22.2		Gross (lb)	62.8 (Display)
Without Speaker	13 (Stand), 6 (Speaker)					