

## ProLite L323W | 81 cm

The new ProLite L323W offers excellent image quality as either a computer monitor or as a TV. With 2 x7W stereo speakers (NICAM Stereo) excellent sound quality is assured. In addition Faroujda technology means that moving images appear crisp and clear.



Technical data	
Panel	32" (80.2cm) IPS TFT LCD
Diagonal	32" (80.2cm)
Display area h x w	687.4 x 412.4 mm
Contrast ratio	500 : 1 typical
Brightness	500 cd / m <sup>2</sup> typical
Response time	33 msec
Viewing zone	horizontal: 170° vertical: 170°
Display colors	16 Mio.
Pixel pitch h x v	0.537 x 0.537 mm
Standard TV	PAL (B/G, I, D/K, L), SECAM (B/G/D/KL), NTSC
Sound	2 x 7W
Inputs	SCART (Composite / RGB), RCA, S-Video
Channels programming TV/AV	99/2
Teletext	FLOF-, TOP-Videotext, Level 1.5
PIP (Picture in Picture)	PC/TV, PC/Video
Picture formats	4:3, 16:9, Zoom 16:9
Remote control	IR remote control, OSD (On Screen Display)
TV equipment	automatic station programming
Horizontal sync	31.47 - 60.24 KHz
Vertical sync	56 - 75 Hz
Bandwidth	103 MHz
Native resolution	1280 x 768
Input connector	DVI-I
Synchronization	Seperate and composite sync
Plug & play	DDC2B
Speaker	2 x 7W
Included accessories	IR remote control (+ batteries), analog and digital signal cable, audio cable (PC), user manual, Info CD
User controls	Brightness, Contrast, H / V Position, Clock, Phase, Treble, Bass, Surround Sound, OSD Position, Full Screen, Economy Mode, Language, Reset, WXGA, Sharpness, Auto Balance, PIP, PIP Control TV Brightness, Contrast, Sharpness, Colour, Tint, Treble, Bass, Surround Sound, OSD Position, Full screen, Economy, Video Mode, Language, Reset, Film Mode, Enhancer, Noise Reducer, Auto Tune, Manual Tune, Channel move
Driver	Windows 95/98/2000/ME/XP
Ergonomics	MPR III
Safety	CE, TÜV GS, FCC-B, UL / C-UL, VCCI-B
Power supply	Worldwide 100-230VAC, 50-60Hz input
power supply	internal
Power usage	180W maximum in normal use, 5W in suspend mode
Power management	Auto power down to standby mode. VESA-DPMS, EPA Energy Star
VESA mounting	200 x 100 mm
Dimensions w x h x d	778 x 480 x 127.5 No Stand 778 x 514 x 300 With Stand "
Weight	21 kg

Version 10/2005, changes and mistakes reserved.