

Fujitsu Plasmavision SlimScreen® P63XHA30WS 63" High Resolution Plasma Monitor



Introducing the Fujitsu P63XHA30WS Plasmavision SlimScreen® monitor. With a 63-inch diagonal screen size, the P63XHA30WS is the largest in Fujitsu's newest line of high resolution Plasmavision SlimScreen monitors. Its sleek and lightweight design allows it to be hung on a wall or placed on a stand to seamlessly integrate into any home theater system. Superior picture quality and natural color display combine with high resolution to display life-like, *and practically life-size*, images. In an industry that strives to produce a visual medium where clarity doesn't decrease with size, Fujitsu goes above and beyond this mission with the introduction of the P63XHA30WS.



- High resolution 1366 x 768 pixel display
- AVM digital video processor
- 16:9 widescreen aspect ratio
- 160° viewing angle
- Slim and lightweight at 4.8" thin* and 158.7 pounds
- Wide range of inputs - SDTV, DTV and HDTV signals
- PC input - both MAC and Windows compatible

63" High Resolution Plasmavision® P63XHA30WS

BRILLIANT COLOR DISPLAY

Using a new 10-bit processing system, the P63XHA30WS produces over 1.07 billion colors to represent on-screen images in their natural color. High brightness and an amazing contrast ratio combine for a brilliant picture display, regardless of room brightness.

PICTURE PERFECT

The P63XHA30WS boasts a DVI-D digital input with HDCP, which provides a direct digital connection to the latest hi-end video devices – such as a satellite system or an HDTV set-top box – to provide crystal-clear high definition digital images.

SLEEK AND STYLISH

Just 4.8" thin*, and 158.7 pounds, the P63XHA30WS is great for custom installations in a wide variety of home theater applications.

CONVERGENT VISUAL MEDIUM

An expanded complement of input terminals for component video, S-video, composite video and analog RGB allow for complete convergence.

IT'S WHAT'S INSIDE™

Fujitsu General has developed the AVM (Advanced Video Movement) digital video signal processor, which virtually eliminates motion artifacts and flicker, improves vertical resolution and reproduces natural movement with ease. The processor's built-in line doubler converts NTSC signals and uses different types of processing for moving and still pictures, yielding smoother images with more natural movement and without visible scan lines.


ACCESS AT YOUR FINGERTIPS

A greater range of picture adjustments is accessible via the improved on-screen menu and supplied remote control. From your seat you can adjust volume and color temperature, select an input source and more!

AWARD WINNING

Since introducing our first plasma display monitor in 1993, Fujitsu Plasmavision SlimScreens have won many awards, including the 2002 Emmy Award for outstanding achievement in technological advancement.

Specifications P63XHA30WS




Display Type	AC-type plasma display panel
Screen Size	54.8" W x 29.3" H (63" diagonal)
Dimensions	59.3" W x 35.3" H x 4.8" D*
Weight	158.7 lbs
Pixel Count	1366 x 768 rectangular
Contrast Ratio	3000:1
Aspect Ratio	16:9
Displayable Colors	1.07 billion colors
Video Standards Supported	NTSC, PAL, SECAM, M-PAL, N-PAL, 4.43NTSC, PAL-60
Video Inputs	Video x 1, s-terminal x 1, component x 2
Audio Inputs	RCA terminal (L/R) x 3 sets, 0.5 Vrms
Computer Inputs	RGB 15-pin x 1
Digital Interface	DVI-D (HDCP) x 1
Viewing Angle	160 degrees
Horizontal kHz	15.62 - 80.00
Vertical Hz	50.0 - 120.0
Power Source	110 - 240 V, AC 50/60 Hz
External Control	RS-232C
Operating Temperature	32°F to 104°F
Relative Humidity	20 to 80 percent (not condensing)
EMC Regulations	FCC part-15 Class B, ICES-003 Class B, AS/NZS3548 Class B, EN55022 Class B
Safety Regulations	UL 6500, U-CL, EN60065, IEC50065

* This is the depth of the main set cabinet. A small input housing adds 0.5" for a total depth of 5.3". This housing does not affect mounting depth when using the Fujitsu P-WB6300B accessory wall bracket.

** Part numbers and dimensions are subject to change. Please check www.plasmavision.com for the latest information.

Specifications are subject to change without notice for further improvement.

Input / Output Array



Optional Accessories**

Desktop Stand, P-TT6300-S

Wall Mount Bracket, P-WB6300-B (adds 2.76" to panel depth at 0° tilt)

Ceiling Mount Bracket, P-CT6300-B

Warranty



Three Year Warranty
on Parts and Labor.

Warranty includes parts & labor and one year on plasma display element.



Fujitsu General America, Inc. • 353 Route 46 West • Fairfield, NJ 07004
Tel: (888) 888-3424 • Fax: (973) 575-2194
www.plasmavision.com