

## **Built for business**

Not just LCD panels. These are productivity panels.

We've designed-in more than 20 years of experience, innovation and leadership in digital projectors to create a line of LCD panels designed for collaboration, presentations, demonstrations, web meetings and video conferencing. InFocus flat panel displays provide the benefits and performance you need in the meeting room and can't find in consumer TVs.

InFocus large format LCD panels deliver gorgeous images and video – at prices that fit your lean budget. They connect easily and automatically with the computer and video sources you use in your business.

### Everything you need in a business-class display

Available in three sizes, InFocus productivity panels deliver full 1080p native resolution and handle computer resolutions up to WUXGA (1920  $\times$  1200) as well as standard and High Definition video signals.

RS232 port allows InFocus productivity panels to integrate easily with Crestron and AMX digital media and room control systems that handle an array of AV sources, computer inputs and lighting controls.

Amplified speakers provide full audio-video support.

The SplitScreen™ feature allows you to display two full-size images or video simultaneously. Focus on the critical content. Easily switch, shrink and enlarge side by side images for emphasis.

#### Your investment is protected:

- Designed for commercial use with durable metal housings and commercial grade power supplies
- Easily upgradable with firmware
- Protected with a 3-year warranty

We did leave one thing out... a high price.





**Connectivity options** 

VGA (HD15) HDMI
Component Video Composite Video
3.5 mm audio in Audio out

RS232 S-Video

Monitor out



### THIN DISPLAYS



	INF4201	INF5501	INF6501
Width	40.2" / 1021 mm	51.5" / 1308 mm	61.7" / 1567 mm
Depth	4.9" / 125 mm	5.3" / 135 mm	6.1" / 155 mm
Height	24.2" / 615 mm	30.6" / 777 mm	37.1" / 942 mm

#### **Optional Accessories**

Wall Mount (SP-INF-WALLMNT) Table Stand (SP-INF-TBLSTND) LiteShow II Wireless Adapter (INLITESHOW2) Cables & Adapters

#### **LiteShow II™**

Eliminate cables and speed set-up time with LiteShow II wireless adapter. Switch presenters in seconds and transmit data, audio, and video over a 300' (95 m) range.

For more information, please visit: www.infocus.com/Accessories.aspx

#### **3-Year Warranty**

All InFocus flat panel displays are backed with a 3-year limited factory warranty. Protect your investment for the long haul with our extended warranty.

For more information, please visit: www.infocus.com/Support/Warranty.aspx





3 YEAR LABOR



Bright Ideas Made Brilliant

INFOCUS CORPORATE HEADQUARTERS 13190 SW 68th Parkway Portland, Oregon 97223-8368, USA

Phone: (1) 503-207-4700 Toll Free: (1) 877-388-8385 Fax: (1) 503-207-1937

INTERNATIONAL HEADQUARTERS 1 Fullerton Road One Fullerton Singapore 049213 Phone: (65) 6513-9600 Fax: (65) 6238-0535

# Specifications &

	INF4201 INF5501 INF6501		
Diagonal Size (Viewable)	INF4201 – 42"		
	INF5501 – 55"		
	INF6501 – 65"		
Panel Technology	a-si TFT Active Matrix LCD		
Surface Treatment	Anti-Glare Coating		
Brightness	450 cd/m <sup>2</sup>		
Native Resolution	1920 × 1080		
Contrast Ratio	5000:1 Native		
Pixel Pitch	INF4201 - 0.019" / .48 mm		
	INF5501 - 0.025" / .63 mm		
	INF6501 - 0.026" / .65 mm		
Display Colors	INF4201 – 16.7 M, True Colors		
	INF5501 – 1.07 G, True Colors		
	INF6501 – 1.07 G, True Colors		
Viewing Angle (H / V)	INF4201 & INF5501 – 176° / 176°		
	INF6501 – 178° / 178°		
Active Area (H × W)	INF4201 – 36.6" × 20.6" / 930 mm × 523 mm		
	INF5501 – 47.6" × 26.8" / 1209 mm × 681 mm		
	INF6501 - 56.2" × 31.6" / 1428 mm × 803 mm		
Power Supply	110 ~ 240 V AC		
Audio	10 W × 2		
Input Sources	VGA (HD15) × 1, S-Video × 1,		
	Composite Video × 1, Component × 1,		
0 1 16	HDMI 1.3 × 2, Audio (3.5 mm Stereo × 1, RCA Stereo × 1)		
Output Sources	Audio (S-PDIG Digital Audio Output) × 1,		
VESA Standard	Control (RS232) × 1		
VESA Standard	INF4201 - 15.7" × 7.9" / 400 mm × 200 mm		
Product Color	INF6501 & INF5501 – 23.6" × 15.7" / 600 mm × 400 mm		
Product Color  Product Weight (without stand)	INF4201 – 77.2 lbs / 35 kg		
Floduct Weight (without Stand)	INF5501 – 92.6 lbs / 42 kg		
	INF6501 – 176.4 lbs / 80 kg		
Shipping Weight	INF4201 – 88.2 lbs / 40 kg		
Shipping weight	INF5501 – 114.6 lbs / 52 kg		
	INF6501 – 231.5 lbs / 105 kg		
Product Dimensions - W×D×H	INF4201 – 40.2" × 4.9" × 24.2" / 1021 mm × 125 mm × 615 mm		
(without stand)	INF5501 – 51.5" × 5.3" × 30.6" / 1308 mm × 135 mm × 777 mm		
(manda stand)	INF6501 – 61.7" × 6.1" × 37.1" / 1567 mm × 155 mm × 942 mm		
Ships With - Accessories	Registration Card, Warranty Card, Quick Start Card,		
	CD with User Manual, Power Cord, VGA Cable, Remote**, Cleaning Cloth		
Menu Language	English		
Operating Temperature	5°C ~ 35°C		
Operating Humidity	90% at 40°C		
Maximum Altitude	10,000 ft / 3098 m		
Product Warranty	3 Years Parts and Labor		
Accessories Warranty	90 Days		
Approvals	FCC B (USA), UL (USA)		

Product specifications, terms, and offerings are subject to change at any time without notice. Batteries not included.











#### For more information, please visit www.infocus.com

©2010 InFocus Corporation. All rights reserved. Specifications are subject to change without further notice. InFocus and InFocus Bright Ideas Made Brilliant are either trademarks or registered trademarks of InFocus Corporation in the United States and other countries. All trademarks are used with permission or are for identification purposes only and are the property of their respective companies. InFocus\_INF\_DS\_EN\_08FEB10. Part Number: MMINFOCUS-0204.