DIAMOND

VIDEO FEATURES

Digital Cable Ready LCD Flat Panel HDTV



MODEL	LT-4260	
Screen Size	42" diagonal, viewable	
Aspect Ratio	Widescreen 16:9	
Finish	Hi-Tech Silver and High Gloss Black	
GENERAL		
DIMENSIONS (ROUNDED TO NEAREST 1/8")		
Height w/ Stand	31.5"	
Width w/ Stand	44.125"	
Depth w/ Stand	14.125"	
Depth w/o Stand	5"	
DISPLAY		
Screen Size	42" diagonal, viewable	
Aspect Ratio	Widescreen 16:9	
Pixel Array	1280 Horizontal x 768 Vertical	
Horizontal Scan Range	31.5kHz - 49kHz	
Vertical Scan Range	60Hz	
SCAN RATE COMPATIBILITY		
Analog Video	NTSC	
Digital TV	480i, 480p, 720p, 1080i (ATSC)	
PC Monitor	VGA, SVGA, XGA, WXGA	

VIDEO FEATURES		
AMVP2™ Motion Processor	•	
Comb Filter Motion-Adaptive 480-Line 3D Y/C		
Automatic Film Mode (3:2 pulldown comp	pensation) •	
DefinEdge™	Selectable by input	
Picture Format Modes for analog 480i/48	30p and 4:3 digital sources 6	
Picture Format Modes for analog 720p/10	080i and digital 16:9 sources 2	
USER INTERFACE		
Control Features		
NetCommand® 4.0	•	
CableCommand™ (Digital Cable Contro	,	
ChannelView™ (On-screen Channel Lis	,	
MediaCommand™ (5-format Memory	Card Reader) JPEG, MP3, WMA	
IR Learning Capabilities	•	
TV Guide On Screen® (8 day interactive pr	rogram guide) •	
PerfectColor™ (six way color adjustment)	•	
PVR Features		
Internal PVR Hard Disc Drive Record	der 120 Gigabit	
	kimately 12 hours HD recording)	
Live TV Pause and Instant Replay	•	
Digitally Record Analog Channels	•	
Digitally Record Digital SD and HD		
Schedule Recordings from TV Guide On S		
Digitally Record from Video/S-Video Devi		
Digitally Record from FireWire® MPEG2 D		
Digitally Playback to FireWire® MPEG2 De	evices •	
PIP/POP Features		
Multi-Image	1 PIP, 3 and 9 POP	
Split Screen	•	
Channel Preview/Input Strobe (analog cha	annels only) •	

TUNING	
Digital/Analog Combined Tuner	Air/Cable - ATSC/NTSC/CableCARD™
2nd Analog Tuner for PIP/POP image	only •

INPUTS ANTENNA (RF) INPUTS

2 Analog/Digital Combined •
CableCARD™ Slot •

AV INPUTS (ANALOG)

A/V Inputs with S-Video with Stereo Audio
Component Video Inputs with Stereo Audio
Input-DTV (YPbPr/RGBHV) with Stereo Audio
1 (480i/480p/720p/1080i)

AV OUTPUTS (ANALOG)

Monitor A/V Output (for recording)


INPUTS/OUTPUTS (DIGITAL)

FireWire® (IEEE 1394) front/rear 1/2
Memory Card Slots for JPEG and MP3 Playback 4 (5-formats)
HDMI™ Input 1
Digital Audio Bitstream Output 1 (coaxial)
Memory Card Slots for JPEG and MP3 Playback 4 (5-formats)

NETCOMMAND® REMOTE CONTROL Fully Illuminated

Features, specifications and dimensions are preliminary and are subject to change.

BACK PANELS:



CableCARD is a trademark of Cable Television Laboratories, Inc.

TV GUIDE, G-LINK and other related marks are registered marks of Gemstar-TV Guide International, Inc. and/or one of its affiliates.

FireWire is a registered trademark of Apple Computer, Inc.

HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.

DTVLink Certification Logo is a U.S. registered mark of CEA.