HP PE4240N 42" Plasma Television

Datasheet





The PE4240N features a bright and high-contrast enhanced definition plasma panel backed by Faroudja's Emmy-Award winning DCDi video processing. Your television is encased in a stylish piano black cabinet, and can be wall mounted or used with the included stand.

Enhanced definition plasma display with 3000:1 contrast

 Enhanced definition plasma display with 3000:1 contrast provides a clear progressively scanned image with rich colors and deep black levels.

Faroudja's Emmy-Award winning DCDi video processing

 Faroudja's Emmy-Award winning DCDi detects low-angle lines and smoothes jagged edges - bringing a new tier of realism to sporting events and movies.

Fine Detail Enhancement

 Fine Detail Enhancement identifies areas of fine detail in a picture, such as skin and hair, and enhances them to a dramatically more life like appearance.

Depth Enhancement

 Depth Enhancement identifies large edges that define separation of objects and enhances them to create a greater perception of depth. The result is a stunning viewing experience.

3D Y/C Digital Comb Filter

 3D Y/C Digital Comb Filter reduces flickering and enhances color purity in complex scenes from broadcast and composite signals from your DVD player or VCR.

FilmMode Processing with 3:2 pull down

 FilmMode Processing with 3:2 pull down accurately reproduces filmoriginated content from video sources

Motion Adaptive Noise Reduction

• Motion Adaptive Noise Reduction greatly enhances quality of off air media and standard definition video.

Cross Color Suppression

• Cross Color Suppression removes cross color artifacts from composite video sources, delivering consistent, true color every time.

Variable aspect ratio support

• Variable aspect ratio support enables scaling of 4:3 video to fill the screen.

DVI-D with HDCP

• DVI-D with HDCP enables pure digital video connections to set top boxes, DVD players, and PCs.

Supports two selectable audio enhancements

- BBE[†]M High Definition Audio—restores clarity and presence for better speech intelligibility and musical realism.
- SRS WOW[™]—creates a bigger, enhanced audio experience by providing three dimensional sound, enhancing musical vocals, and creating the perception of deep, rich bass.

Picture-in-Picture and Split Screen Display

 Picture-in-Picture and Split Screen Display enables simultaneous viewing of two different channels or sources.

Svelte, wall-mountable design

• Svelte, wall-mountable design is only 4.3 inches (110 millimeters) thick.

Universal Remote Control

 Universal Remote Control controls additional components, including HP Media Center PCs and HP Digital Entertainment Centers.

Product features are dependent upon the input used.



HP PE4240N 42" Plasma Television

Datasheet

Key Television Specifications

Panel System	Enhanced Definition Plasma Display	Displayable Colors	Up to 16.7 Million
Video Format	Accepts RGB, NTSC, 480i, 480p, 720p, 1080i Converts all video signals to 480p enhanced definition video	Pixel Pitch	0.043 in. (H) \times 0.043 in. (V) 1.08 (H) \times 1.08 (V) m
		Anti-reflective Coating	Yes
Diagonal Screen Size	42 in. (1066.8mm)	Life'	Up to 60,000 Hrs
nches)		Contrast (typical)	3000 : 1
iewable Image (W x H)	36.3 in. x 20.4 in (921 mm X 518 mm)	Brightness (typical before filter)	Up to 1000 cd/m ²
spect Ratio	16:9 Widescreen		
lative Resolution	852 (H) × 480 (V) pixels		

Tuner Specifications

TV Tuner	Built-in NTSC TV Tuner	Cable Tuning System	Standard, HRC, IRC
Tuning options Channel Coverage	Automatic channel scan	Closed Caption	Yes
	Automatic Fine Tuning	MTS Sound Processing	Stereo, mono, SAP
	Favorite channel edit A/B hot channel buttons	V-Chip	Password protect viewing according to Age and Content Ratir TV Rating, and MPAA Rating TV System
	VHF 2 – 13 UHF 14 – 69 CATV 1 – 125	HDTV supported inputs	Component Input (YPbPr): 1080i/720p/480p/480i DVI: 1080i/720p/480p2
Antenna	75 Ohm External		

Television Control Specifications

Universal Remote Control

Programmable universal remote controls TV and additional devices, including HP Digital Entertainment Centers and HP Media Center PCs.

Front Controls

Additional Features

Auto Channel Program Channel Skip/Add Favorite Channel A & B Aspect Modes – 4:3, 16:9, Zoom 1, Zoom 2 Sleep timer Closed Caption V-Chip Parental Control

Television Connections Specifications

Antenna Input (75 Ohm F connector)	1
High Definition Component Input (YPbPr)	1
Standard Definition Component Input (YPbPr)	1
Composite Video Input (AV)	2
S-Video Input	2
PC Input (RGB-VGA)	1
DVI-HDCP Interface	1 (with HDCP support)
A/V Audio Inputs	6
PC Audio Inputs	2
Audio Out - RCA Pair	1
RS-232 (for service)	1

Down, Channel Up, and Channel Down

Power, Input, Menu, Setting, Adjust/Volume Up, Adjust/Volume



HP PE4240N 42" Plasma Television

Television Power Specifications

Input Power	120/240V	Average	380 watts
Nominal Current	3.5 A maximum	Integrated Power Supply	Yes
requency	50 Hz ~ 60 Hz	Power Cable Length	70 in (1.8 m); Detachable
key Audio Specific	ations		
Speakers	Integrated 5W x 2, rear firing	MTS / SAP	Yes – Stereo, Mono, SAP
Sound modes	SRS WOW: Creates a bigger, enhanced audio experience by	Audio out	1 (RCA Pair)
	providing three dimensional sound, enhancing musical vocals, and creating the perception of deep, rich bass without the need for a subwoofer	Audio Controls	Bass/Treble/Volume/Balance
	BBE™ High Definition Audio: Restores clarity and presence for		
Television Weights	better speech intelligibility and musical realism.	Environmental Specific	ations
-	better speech intelligibility and musical realism. and Dimensions Panel w/ stand (h x w x d)	Humidity – Operating	20% to 80% (no condensation)
Television Weights Dimensions	better speech intelligibility and musical realism.	Humidity – Operating Humidity – Non-operating Altitude – Operating	20% to 80% (no condensation) 5% to 80% (38.7°C maximum wet bulb temperature) 0 to 6,562 ft. (0 to 2,000 m)
-	and Dimensions Panel w/ stand (h x w x d) 27.78 in x 40.8 in x 9.68 in (708.5 mm x 1038 mm x 245.9 mm) Panel without stand (h x w x d)	Humidity – Operating Humidity – Non-operating	20% to 80% (no condensation) 5% to 80% (38.7°C maximum wet bulb temperature
-	and Dimensions Panel w/ stand (h x w x d) 27.78 in x 40.8 in x 9.68 in (708.5 mm x 1038 mm x 245.9 mm) Panel without stand (h x w x d) 25.2 in x 40.8 in x 4.3 in (640 mm x 1038 mm x 110 mm) Stand Footprint (h x d x w) 7.1 in x 28.2 in x 9.68 in (180 mm x 716 mm x 245.9mm) Packaged (h x d x w)	Humidity – Operating Humidity – Non-operating Altitude – Operating	20% to 80% (no condensation) 5% to 80% (38.7°C maximum wet bulb temperature) 0 to 6,562 ft. (0 to 2,000 m)
Dimensions	Panel w/ stand (h x w x d) 27.78 in x 40.8 in x 9.68 in (708.5 mm x 1038 mm x 245.9 mm) Panel without stand (h x w x d) 25.2 in x 40.8 in x 4.3 in (640 mm x 1038 mm x 110 mm) Stand Footprint (h x d x w) 7.1 in x 28.2 in x 9.68 in (180 mm x 716 mm x 245.9 mm) Packaged (h x d x w) 37.4 in x 17.9 in x 38.0 in (950 mm x 455 mm x 1220 mm) Panel (Display head)	Humidity – Operating Humidity – Non-operating Altitude – Operating	20% to 80% (no condensation) 5% to 80% (38.7°C maximum wet bulb temperature 0 to 6,562 ft. (0 to 2,000 m)

Ships attached and is removable Base 41°F to 95°F (5°C to 35°C) **Temparature - Operating**

108 lbs (49 kg)

Temperature - Non-operating -4°F to 140°F (-20°C to 60°C)

Accessories, Warranty and Agency Approvals

Quick Start Guide	Wall Mountable	Yes - with optior
Instruction Manual	Certification and Compliance	FCC Approval
Remote Control		UL Approval
75 Ohm Coaxial Cable	Warranty	l year, parts an
Power Cable		
HP High Definition Tuner HP Digital Entertainment Center HP Media Center PC		
	Instruction Manual Remote Control 75 Ohm Coaxial Cable Power Cable HP High Definition Tuner HP Digital Entertainment Center	Instruction Manual Certification and Compliance Remote Control 75 Ohm Coaxial Cable Warranty Power Cable HP High Definition Tuner HP Digital Entertainment Center

DCDi[®] SRS(•) WOW **by**FAROUDJA DIGITAL

SRS WOW and the (●) symbol are trademarks of SRS Labs, Inc. BBE and the BBE logo are registered trademarks or trademarks of BBE Sound, Inc. DCDi™ is a trademark of Faroudja, a division of Genesis Microchip Inc.

Product Number: P8719AA#ABA 09/04

Actual product may vary from image shown on datasheet. HP shall not be liable for technical or editorial errors or omissions contained herein. All hardware and software specifications are subject to change without notice. Copyright © 2004 HewlettPackard Development Company, LP. SRS WOW and the (●)' symbol are trademarks of SRS Labs, Inc. BBE and the BBE logo are registered trademarks of BBE Sound, Inc. DCDi® by Faroudja is a registered trademark of Genesis Microchip Inc.

Questions about the HP PL4245N 42" HD-Ready Plasma Television? Look us up online at http://www.hp.com



Yes - with optional Wall Mount (Wall Mount sold separately)

UL Approval 1 year, parts and labor

Datasheet