

## LME-32X8

1. 32" 16:9 WXGA LCD Display
2. 16.77 Million Colors
3. High Contrast Ratio (800:1)
4. High Brightness (550 cd/m<sup>2</sup>)
5. Pixel Resolutions 1366 x 768 Pixels
6. Multi-scanning PC Monitor Support Up to 1280 x 1024
7. 170 Degrees Viewing Angle
8. RS-232 Control Port
9. Built-In Speaker: 10W + 10W



Specification	LME-32X8
<b>Display</b>	
Screen Size	697.689 mm x 392.26 mm (32" Diagonal)
Aspect Ratio	16 : 9
Number of Pixels	1366 (H) x 768 (V)
Pixel Pitch	0.4215 mm (H) x 0.4215 mm (V)
Contrast Ratio	800 : 1
Brightness	550 cd/m <sup>2</sup>
Displayable Colors	16.77 Million Colors
Viewing Angle	170°
Response Time	25 msec
<b>Signals</b>	
Synchronization (Auto Detect)	
Horizontal Frequency	15KHz / 31~69 KHz
Vertical Frequency	50~85 Hz
Video System	480i, 480p, 720p, 1080i SDTV/EDTV/HDTV, NTSC
RGB Resolution	Up to 1280 x 1024 (SXGA)
<b>RGB/DVI</b>	
DVI Input (with HDCP)	DVI-D 24 pin x 1
RGB Input	D-Sub 15-pin x 1
RGB Output	D-Sub 15-pin x 1
Audio Input	RCA-pin (L/R) x 2 Sets
<b>Audio</b>	
Inner Speaker Output	10W x 2
<b>Video Capability</b>	
NTSC Tuner Input	RF 181CH x 1
Composite Video Input	RCA-pin x 2
S-Video Input	Mini DIN 4-pin x 2
Component Video Input	RCA-pin x 2 Sets (Y/CB/CR, Y/PB/PR auto detect)
Audio Input	RCA-pin (L/R) x 4 Sets
Audio Output	RCA-pin (L/R) x 1 Set
External Subwoofer Output	RCA-pin Type x 1
<b>Control Port</b>	
RS-232	D-Sub 9-pin x 1
<b>General</b>	
Power Supply	110V~240V/50~60Hz