

L42 HDTV

THIS STATE-OF-THE-ART 42" LIQUID CRYSTAL HIGH DEFINITION TELEVISION CAN EASILY ENHANCE THE DECOR OF ANY FAMILY ROOM, LIVING ROOM OR DEN. WITH SUPERIOR RESOLUTION AND BREATHTAKING COLOR PURITY, THE VIZIO L42 IS THE NEXT-GENERATION TV TO CARRY YOU INTO THE HIGH DEFINITION FUTURE.

www.viziotv.com







FEATURES

- 2 42" Diagonal, 16:9 Aspect Ratio, Active Matrix TFT Liquid Crystal Display (LCD)
- 2 High Definition Television (HDTV) with a native resolution of 1366 x 768
- Industry leading 800:1 Contrast Ratio
- Built-in HDTV digital tuner supporting NTSC/ATSC local HD and digital channels via antenna, and unscrambled HD and digital cable channels
- 12 High Brightness (500 cd/m²) providing a more vivid, brilliant picture in any environment
- 2 30-bit color depth supporting 16.7 million colors
- Multiple video format support with HDMI, component video, composite video, S-Video and RF antenna inputs allows you to enjoy video from a variety of sources
- 2 Wide viewing angle (178°) so that everyone can view the picture from practically anywhere in the room
- D
 PIP (Picture in Picture) and POP (side-by-side) for ultimate video enjoyment while watching 2 video programs at the same time
- 50,000 Hour Lamp Life provides over 27 years of use before half brightness (based on an average of 6 hours / day use)
- VIZIO Universal Remote Control and stand included





VIZIO VIP SERVICES Extended Warranties, Installation Services WWW.VIZIOTV.COM



SPECIFICATIONS

- Dentel: 42" diagonal, 16:9 Widescreen, Active Matrix TFT Liquid Crystal Display
- Resolution: 1366 x 768 pixels
- Display Compatibility: HDTV (720P)
- Signal Compatibility: 480i (SDTV), 480P (EDTV), 720P (HDTV), 1080i (HDTV)
- Response Time: 8ms
- Brightness: 500 cd/m2 typical
- > Contrast: 800:1 typical
- Viewing Angle: 178° (horizontal/vertical)
- Tuners: NTSC Standard Analog TV, ATSC HDTV off-air Digital TV and clear QAM digital cable
- Inputs: 1x RF (F Connector for internal ATSC/QAM/NTSC Tuner) 2x HDMI with HDCP plus Stereo Analog Audio 2x Component YPbPr plus Stereo Audio 2x Composite Video / 1x S-Video plus Stereo Audio 1x Analog RGB plus Stereo Audio
- Outputs: 1x SPDIF Digital Audio 1x Stereo Analog Audio
- Speakers: 2 x 10 W



* Product specifications are subject to change without obligation

- Features: PIP, POP, CC, V-Chip, Noise Reduction, 3D Comb Filter, Zoom, Freeze, Motion Adaptive De-Interlace, 3:2 Pull-down, ATSC, with 8VSB & QAM demodulation, with MPEG-2 decoding, NTSC Video decoding via RF (Antenna, Cable or Satellite) or Video (CVBS, S-Video or Component), Progressive Scan Video via Component YPbPr, VGA or HDMI, HDTV via HDMI or Component YPbPr, Computer 640x480, 800x600, 1024x768 via VGA or 640x480 via HDMI, SRS Sound enhancement, Color Temperature of 6500K, 5400K and 9300K, Independent Red, Green and Blue adjustment for user fine tuning of color temperature.
- **Power:** IEC Connector for direct power line connection
- Voltage Range: 100-240 VAC at 50/60 Hz
- > Power consumption: 280 W average
- Dimensions: 28.81in (H) x 41.26in (W) x 4.29in (D) / 732mm (H) x 1048mm (W) x 109mm (D) without Stand 29.84in (H) x 41.26in (W) x 11.42in (D) / 758mm (H) x 1048mm (W) x 290mm (D) with Stand
- Net Weight: 73.33 lbs (33.2 kg) with Stand
- Agency Approvals: UL, C-UL, FCC Class B





Tilt Wall Mount, Flush Wall Mount, HDMI cables,Component video cables - Call **1.888.849.4623** for details.





WHERE VISION MEETS VALUE